



## Safety Data Sheet

Copyright, 2023, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

|                        |           |                         |          |
|------------------------|-----------|-------------------------|----------|
| <b>Document Group:</b> | 22-0537-5 | <b>Version Number:</b>  | 6.05     |
| <b>Issue Date:</b>     | 11/28/23  | <b>Supersedes Date:</b> | 10/03/22 |

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Scotch-Weld™ Epoxy Adhesive 460NS Off-White, Part A

#### Product Identification Numbers

62-2892-8530-6  
7010329565

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Structural adhesive

#### 1.3. Supplier's details

|                      |   |
|----------------------|---|
| <b>MANUFACTURER:</b> | 3M                                      |
| <b>DIVISION:</b>     | Industrial Adhesives and Tapes Division |
| <b>ADDRESS:</b>      | 3M Center, St. Paul, MN 55144-1000, USA |
| <b>Telephone:</b>    | 1-888-3M HELPS (1-888-364-3577)         |

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

#### 2.1. Hazard classification

Serious Eye Damage/Irritation: Category 1.

Skin Corrosion/Irritation: Category 1B.

Skin Sensitizer: Category 1.

#### 2.2. Label elements

##### Signal word

Danger

##### Symbols

Corrosion | Exclamation mark |

##### Pictograms

**Hazard Statements**

Causes severe skin burns and eye damage.  
May cause an allergic skin reaction.

**Precautionary Statements****Prevention:**

Do not breathe dust/fume/gas/mist/vapors/spray.  
Wear protective gloves, protective clothing, and eye/face protection.  
Wash thoroughly after handling.  
Contaminated work clothing must not be allowed out of the workplace.

**Response:**

IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
Immediately call a POISON CENTER or doctor/physician.  
If skin irritation or rash occurs: Get medical advice/attention.  
Wash contaminated clothing before reuse.  
IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

**Storage:**

Store locked up.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**2.3. Hazards not otherwise classified**

May cause chemical gastrointestinal burns.

**Supplemental Information:**

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

**SECTION 3: Composition/information on ingredients**

| Ingredient   | C.A.S. No.    | % by Wt                |
|--|---------------|------------------------|
| Modified Epoxy Resin (NJTS Reg. No. 04499600-6840) | Trade Secret* | 40 - 70 Trade Secret * |
| 4,7,10-Trioxatridecane-1,13-Diamine                | 4246-51-9     | 30 - 60 Trade Secret * |
| 2,4,6-tris((Dimethylamino)-Methyl)Phenol           | 90-72-2       | 1 - 5 Trade Secret *   |
| Amorphous Silica                                   | 67762-90-7    | 1 - 5 Trade Secret *   |

NJTS or NJTSRN: New Jersey Trade Secret Registry Number.

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

**SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

**Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin Contact:**

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

**Eye Contact:**

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

**If Swallowed:**

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Skin burns (localized redness, swelling, itching, intense pain, blistering, and tissue destruction). Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision).

#### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

#### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

#### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

#### Hazardous Decomposition or By-Products

**Substance**

Aldehydes  
Carbon monoxide  
Carbon dioxide  
Hydrogen Chloride  
Oxides of Nitrogen

**Condition**

During Combustion  
During Combustion  
During Combustion  
During Combustion  
During Combustion

#### 5.3. Special protective actions for fire-fighters

When fire fighting conditions are severe and total thermal decomposition of the product is possible, wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

#### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

For industrial/occupational use only. Not for consumer sale or use. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

**7.2. Conditions for safe storage including any incompatibilities**

Store away from acids. Store away from strong bases. Store away from oxidizing agents. Store away from amines.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient        | C.A.S. No. | Agency | Limit type   | Additional Comments |
|-------------------|------------|--------|--|---------------------|
| SILICA, AMORPHOUS | 67762-90-7 | OSHA   | TWA:20 millions of particles/cu. ft.;TWA concentration:0.8 mg/m3 |                     |

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

**8.2. Exposure controls****8.2.1. Engineering controls**

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

**8.2.2. Personal protective equipment (PPE)****Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

**Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl Rubber

Fluoroelastomer

Nitrile Rubber

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Butyl rubber

Apron – Nitrile

Apron - polymer laminate

### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Appearance

Physical state

Liquid

Color

Amber

**Specific Physical Form:**

viscous liquid

**Odor**

Very Mild Odor, Pungent Odor

**Odor threshold**

*No Data Available*

**pH**

*Not Applicable*

**Melting point**

*Not Applicable*

**Boiling Point**

$\geq 171$  °C

**Flash Point**

340 °F [*Test Method*:Closed Cup]

**Evaporation rate**

*No Data Available*

**Flammability (solid, gas)**

Not Applicable

**Flammable Limits(LEL)**

*No Data Available*

**Flammable Limits(UEL)**

*No Data Available*

**Vapor Pressure**

$\leq 3.0$  mmHg [*@* 68 °F]

**Vapor Density**

3.72 [*Ref Std*:AIR=1]

**Density**

1.09 g/ml

**Specific Gravity**

1.09 [*Ref Std*:WATER=1]

**Solubility in Water**

Slight (less than 10%)

**Solubility- non-water**

*No Data Available*

**Partition coefficient: n-octanol/ water**

*No Data Available*

**Autoignition temperature**

*No Data Available*

**Decomposition temperature**

*No Data Available*

**Viscosity**

8,000 - 16,000 centipoise [*@* 73.4 °F ] [*Test Method*:Brookfield]

**Hazardous Air Pollutants**

0 % weight [*Test Method*:Calculated]

**Molecular weight**

*No Data Available*

**VOC Less H2O & Exempt Solvents**

0 g/l [*Test Method*:calculated SCAQMD rule 443.1]

VOC Less H2O & Exempt Solvents

[Details: when used as intended with Part B]  
0 g/l [Test Method: calculated SCAQMD rule 443.1] [Details: as supplied]

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

None known.

### 10.5. Incompatible materials

Amines  
Alcohols  
Strong bases  
Strong acids  
Strong oxidizing agents

### 10.6. Hazardous decomposition products

| <u>Substance</u> | <u>Condition</u> |
|------------------|------------------|
| None known.      |                  |

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

#### Skin Contact:

Corrosive (Skin Burns): Signs/symptoms may include localized redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

**Eye Contact:**

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

**Ingestion:**

Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen.

**Additional Information:**

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

| Name                                     | Route                          | Species | Value  |
|--|--------------------------------|---------|--|
| Overall product                          | Dermal                         |         | No data available; calculated ATE >5,000 mg/kg |
| Overall product                          | Ingestion                      |         | No data available; calculated ATE >5,000 mg/kg |
| 4,7,10-Trioxatridecane-1,13-Diamine      | Dermal                         | Rabbit  | LD50 2,525 mg/kg                               |
| 4,7,10-Trioxatridecane-1,13-Diamine      | Ingestion                      | Rat     | LD50 2,850 mg/kg                               |
| Amorphous Silica                         | Dermal                         | Rabbit  | LD50 > 5,000 mg/kg                             |
| Amorphous Silica                         | Inhalation-Dust/Mist (4 hours) | Rat     | LC50 > 0.691 mg/l                              |
| Amorphous Silica                         | Ingestion                      | Rat     | LD50 > 5,110 mg/kg                             |
| 2,4,6-tris((Dimethylamino)-Methyl)Phenol | Dermal                         | Rat     | LD50 1,280 mg/kg                               |
| 2,4,6-tris((Dimethylamino)-Methyl)Phenol | Ingestion                      | Rat     | LD50 1,000 mg/kg                               |

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

| Name                                     | Species       | Value                     |
|--|---------------|---------------------------|
| Overall product                          | In vitro data | Corrosive                 |
| 4,7,10-Trioxatridecane-1,13-Diamine      | Rabbit        | Corrosive                 |
| Amorphous Silica                         | Rabbit        | No significant irritation |
| 2,4,6-tris((Dimethylamino)-Methyl)Phenol | Rabbit        | Corrosive                 |

**Serious Eye Damage/Irritation**

| Name                                     | Species | Value                     |
|--|---------|---------------------------|
| 4,7,10-Trioxatridecane-1,13-Diamine      | Rabbit  | Corrosive                 |
| Amorphous Silica                         | Rabbit  | No significant irritation |
| 2,4,6-tris((Dimethylamino)-Methyl)Phenol | Rabbit  | Corrosive                 |

**Skin Sensitization**

| Name                                     | Species                | Value          |
|--|------------------------|----------------|
| 4,7,10-Trioxatridecane-1,13-Diamine      | Professional judgement | Sensitizing    |
| Amorphous Silica                         | Human and animal       | Not classified |
| 2,4,6-tris((Dimethylamino)-Methyl)Phenol | Guinea pig             | Not classified |

**Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

### Germ Cell Mutagenicity

| Name                                     | Route    | Value         |
|--|----------|---------------|
| Overall product                          | In Vitro | Not mutagenic |
| 4,7,10-Trioxatridecane-1,13-Diamine      | In Vitro | Not mutagenic |
| Amorphous Silica                         | In Vitro | Not mutagenic |
| 2,4,6-tris((Dimethylamino)-Methyl)Phenol | In Vitro | Not mutagenic |

### Carcinogenicity

| Name             | Route         | Species | Value  |
|------------------|---------------|---------|--|
| Amorphous Silica | Not Specified | Mouse   | Some positive data exist, but the data are not sufficient for classification |

### Reproductive Toxicity

#### Reproductive and/or Developmental Effects

| Name                                | Route     | Value                                  | Species | Test Result           | Exposure Duration          |
|-------------------------------------|-----------|--|---------|-----------------------|----------------------------|
| 4,7,10-Trioxatridecane-1,13-Diamine | Ingestion | Not classified for female reproduction | Rat     | NOAEL 600 mg/kg/day   | prematuring into lactation |
| 4,7,10-Trioxatridecane-1,13-Diamine | Ingestion | Not classified for male reproduction   | Rat     | NOAEL 600 mg/kg/day   | 59 days                    |
| 4,7,10-Trioxatridecane-1,13-Diamine | Ingestion | Not classified for development         | Rat     | NOAEL 600 mg/kg/day   | prematuring into lactation |
| Amorphous Silica                    | Ingestion | Not classified for female reproduction | Rat     | NOAEL 509 mg/kg/day   | 1 generation               |
| Amorphous Silica                    | Ingestion | Not classified for male reproduction   | Rat     | NOAEL 497 mg/kg/day   | 1 generation               |
| Amorphous Silica                    | Ingestion | Not classified for development         | Rat     | NOAEL 1,350 mg/kg/day | during organogenesis       |

### Target Organ(s)

#### Specific Target Organ Toxicity - single exposure

| Name                                     | Route      | Target Organ(s)        | Value  | Species                | Test Result         | Exposure Duration |
|--|------------|------------------------|--|------------------------|---------------------|-------------------|
| 4,7,10-Trioxatridecane-1,13-Diamine      | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | similar health hazards | NOAEL Not available |                   |
| 2,4,6-tris((Dimethylamino)-Methyl)Phenol | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification |                        | NOAEL Not available |                   |

#### Specific Target Organ Toxicity - repeated exposure

| Name                                | Route      | Target Organ(s)   | Value          | Species | Test Result         | Exposure Duration |
|-------------------------------------|------------|---|----------------|---------|---------------------|-------------------|
| 4,7,10-Trioxatridecane-1,13-Diamine | Ingestion  | gastrointestinal tract   heart   endocrine system   bone, teeth, nails, and/or hair   hematopoietic system   liver   immune system   muscles   nervous system   eyes   kidney and/or bladder   respiratory system   vascular system | Not classified | Rat     | NOAEL 600 mg/kg/day | 59 days           |
| Amorphous Silica                    | Inhalation | respiratory system  | Not classified | Human   | NOAEL Not           | occupational      |



|  |        |   |                |     |                     |          |
|--|--------|---|----------------|-----|---------------------|----------|
|  |        | silicosis   |                |     | available           | exposure |
| 2,4,6-tris((Dimethylamino)-Methyl)Phenol | Dermal | skin   liver   nervous system   auditory system   hematopoietic system   eyes | Not classified | Rat | NOAEL 125 mg/kg/day | 28 days  |

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information**

**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

**Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

**SECTION 13: Disposal considerations**

**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

**SECTION 14: Transport Information**

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

**SECTION 15: Regulatory information**

**15.1. US Federal Regulations**

Contact 3M for more information.

**EPCRA 311/312 Hazard Classifications:**

|                         |
|-------------------------|
| <b>Physical Hazards</b> |
| Not applicable          |

|                       |
|-----------------------|
| <b>Health Hazards</b> |
|-----------------------|

|  |
|--|
| Hazard Not Otherwise Classified (HNOC) |
| Respiratory or Skin Sensitization      |
| Serious eye damage or eye irritation   |
| Skin Corrosion or Irritation           |

## 15.2. State Regulations

Contact 3M for more information.

## 15.3. Chemical Inventories

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

## 15.4. International Regulations

Contact 3M for more information.

|  |
|--|
| <b>This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.</b> |
|--|

## SECTION 16: Other information

### NFPA Hazard Classification

**Health:** 3 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

|                        |           |                         |          |
|------------------------|-----------|-------------------------|----------|
| <b>Document Group:</b> | 22-0537-5 | <b>Version Number:</b>  | 6.05     |
| <b>Issue Date:</b>     | 11/28/23  | <b>Supersedes Date:</b> | 10/03/22 |

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

**3M USA SDSs are available at [www.3M.com](http://www.3M.com)**