



Revision Number: 002.3

Issue date: 09/03/2014

### 1. PRODUCT AND COMPANY IDENTIFICATION

<b>Product name:</b>	<b>BONDERITE M-CR T5900 RTU AERO</b> known as <b>ALODINE T 5900 RTU</b>	<b>IDH number:</b>	772743
<b>Product type:</b>	Conversion coating	<b>Region:</b>	United States
<b>Restriction of Use:</b>	None identified	<b>Contact information:</b>	
<b>Company address:</b>	Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067	Telephone:	(860) 571-5100
		MEDICAL EMERGENCY Phone:	Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711
		TRANSPORT EMERGENCY Phone:	CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887
		Internet:	www.henkelna.com

### 2. HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW

**WARNING:** MAY CAUSE AN ALLERGIC SKIN REACTION.

HAZARD CLASS	HAZARD CATEGORY
SKIN SENSITIZATION	1

#### PICTOGRAM(S)



#### Precautionary Statements

<b>Prevention:</b>	Avoid breathing vapors, mist, or spray. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves.
<b>Response:</b>	IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical attention. Wash contaminated clothing before reuse.
<b>Storage:</b>	Not prescribed
<b>Disposal:</b>	Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Dipotassium hexafluorozirconate	16923-95-8	0.1 - 1
Chromium compound	Proprietary	0.1 - 1

\* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

#### 4. FIRST AID MEASURES

<b>Inhalation:</b>	If mist or vapor of this product is inhaled, remove person immediately to fresh air. Seek medical attention if symptoms develop or persist.
<b>Skin contact:</b>	Immediately flush skin with plenty of water (using soap, if available). If symptoms develop and persist, get medical attention.
<b>Eye contact:</b>	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
<b>Ingestion:</b>	Get immediate medical attention. DO NOT induce vomiting unless directed to do so by medical personnel.
<b>Symptoms:</b>	See Section 11.

#### 5. FIRE FIGHTING MEASURES

<b>Extinguishing media:</b>	Use media appropriate for surrounding material.
<b>Special firefighting procedures:</b>	Wear full protective clothing. Wear self-contained breathing apparatus.
<b>Unusual fire or explosion hazards:</b>	This product is an aqueous mixture which will not burn.
<b>Hazardous combustion products:</b>	Irritating and/or toxic fumes and gases may be emitted upon the product's decomposition.

#### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

<b>Environmental precautions:</b>	Prevent further leakage or spillage if safe to do so. Wear appropriate protective equipment and clothing during clean-up.
<b>Clean-up methods:</b>	Absorb spill with inert material. Shovel material into appropriate container for disposal. Dispose of according to Federal, State and local governmental regulations.

#### 7. HANDLING AND STORAGE

<b>Handling:</b>	Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Provide adequate ventilation. Do not take internally. For industrial use only.
<b>Storage:</b>	For safe storage, store between 40 °F (4.4 °C) and 100 °F (37.8 °C) Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Protect from freezing.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Dipotassium hexafluorozirconate	5 mg/m <sup>3</sup> TWA (as Zr) 10 mg/m <sup>3</sup> STEL (as Zr) 2.5 mg/m <sup>3</sup> TWA (as F)	5 mg/m <sup>3</sup> PEL (as Zr) 2.5 mg/m <sup>3</sup> PEL (as F) 2.5 mg/m <sup>3</sup> TWA Dust.	None	None
Chromium compound	None	1 mg/m <sup>3</sup> PEL (as Cr) 0.5 mg/m <sup>3</sup> PEL (as Cr)	None	None

<b>Engineering controls:</b>	Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.
<b>Respiratory protection:</b>	If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or vapors, appropriate NIOSH/MSHA respiratory protection must be provided.
<b>Eye/face protection:</b>	Wear safety glasses; chemical goggles for fumes which may arise from thermal processing.
<b>Skin protection:</b>	Chemical resistant, impermeable gloves. Use of impervious apron and boots are recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Liquid
<b>Color:</b>	Green
<b>Odor:</b>	Mild
<b>Odor threshold:</b>	Not available.
<b>pH:</b>	3.8 - 4.0
<b>Vapor pressure:</b>	Not determined
<b>Boiling point/range:</b>	> 100 °C (> 212°F) calculated
<b>Melting point/ range:</b>	Not determined
<b>Specific gravity:</b>	1.00 - 1.02 at 22.2 °C (71.96 °F)
<b>Vapor density:</b>	Not available.
<b>Flash point:</b>	Not applicable
<b>Flammable/Explosive limits - lower:</b>	Not available.
<b>Flammable/Explosive limits - upper:</b>	Not available.
<b>Autoignition temperature:</b>	Not applicable
<b>Evaporation rate:</b>	Not determined
<b>Solubility in water:</b>	Complete
<b>Partition coefficient (n-octanol/water):</b>	Not available.
<b>VOC content:</b>	Not available.
<b>Viscosity:</b>	Not available.
<b>Decomposition temperature:</b>	Not available.

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Stable at normal conditions.
<b>Hazardous reactions:</b>	Will not occur.
<b>Hazardous decomposition products:</b>	Irritating and/or toxic fumes and gases may be emitted upon the product's decomposition.
<b>Incompatible materials:</b>	This product may react with strong oxidizing agents.
<b>Reactivity:</b>	Not available.
<b>Conditions to avoid:</b>	Avoid excessive heat and ignition sources.

## 11. TOXICOLOGICAL INFORMATION

**Relevant routes of exposure:** Skin, Inhalation, Eyes

**Potential Health Effects/Symptoms**

<b>Inhalation:</b>	This product is irritating to the respiratory system.
<b>Skin contact:</b>	This product may cause irritation to the skin. This product contains a component that may cause allergic skin reactions.
<b>Eye contact:</b>	This product may cause irritation to the eyes.
<b>Ingestion:</b>	Ingestion of this product may cause nausea, vomiting and diarrhea.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Dipotassium hexafluorozirconate	None	Allergen, Blood, Cardiac, Central nervous system, Corrosive, Gastrointestinal tract, Irritant, Kidney, Lung, Metabolic, Muscle, Teeth, Less weight gain and food intake.
Chromium compound	None	Allergen, Corrosive, Irritant, Respiratory

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Dipotassium hexafluorozirconate	No	No	No
Chromium compound	No	No	No

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal.

**Hazardous waste number:** This product contains chromium which is a hazardous waste (D007).

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

### U.S. Department of Transportation Ground (49 CFR)

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

### International Air Transportation (ICAO/IATA)

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

### Water Transportation (IMO/IMDG)

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

## 15. REGULATORY INFORMATION

### United States Regulatory Information

**TSCA 8 (b) Inventory Status:** All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.  
**TSCA 12 (b) Export Notification:** None above reporting de minimis  
**CERCLA/SARA Section 302 EHS:** None above reporting de minimis  
**CERCLA/SARA Section 311/312:** Immediate Health, Delayed Health  
**CERCLA/SARA Section 313:** None above reporting de minimis  
**California Proposition 65:** No California Proposition 65 listed chemicals are known to be present.

### Canada Regulatory Information

**CEPA DSL/NDL Status:** All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

## 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format.

**Prepared by:** John DiCerbo, Sr. Regulatory Affairs Specialist

**Issue date:** 09/03/2014

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.