

SM5130

Sealant tape

Ideally suited to aerospace applications

Features

- Predominantly used as a debulk tape in aerospace applications.
- Low tack for ease of bag repositioning.
- Strips cleanly and quickly after curing, on cooling below 66°C (151°F).
- Manufactured by Schnee Morehead in the USA.

Properties

Maximum cure temperature	204°C	400°F
Colour	Grey	

Availability

Roll size	9.14m x 12mm x 3mm	30ft x 0.5in x 0.125in
Standard box contents	32 rolls per box	

Storage

Must be stored in its original containers, below 27°C (81°F).
Material has a 9 month shelf life from date of manufacture.
Must be stored flat.
Boxes should be stacked no more than 5 high.

Health & safety

Handling of these products must conform to individual company guidelines and health and safety regulations.

All statements, technical information and recommendations contained in this data sheet are given in good faith and are based on tests believed to be reliable, but their accuracy and completeness are not guaranteed. They do not constitute an offer to any person and shall not be deemed to form the basis of any subsequent contract. All products are sold subject to the Cytec's Standard Terms and conditions of Sale. Accordingly, the user shall determine the suitability of the products for their intended use prior to purchase and shall assume all risk and liability in connection therewith. It is the responsibility of those wishing to sell items made from or embodying the products to inform the user of the properties of the products and the purposes for which they may be suitable, together with all precautionary measures required in handling those products. The information contained herein is under constant review and liable to be modified from time to time.
© Copyright 2012 – Cytec Process Materials (Keighley) Ltd, Cytec Process Materials (CA) Inc, Cytec Process Materials (Toulouse) Sarl, Cytec Process Materials (Milan) Srl. All rights reserved worldwide. All trademarks or registered trademarks are the property of their respective owners.