

# tesa® 64613

Utility grade duct tape

## PRODUCT INFORMATION

### Product Description

tesa® 64613 is a high-shear and high-tensile poly-coated cloth tape providing easy hand-tearability and adhesion to a variety of different surfaces. It shows easy unwind and straight edge tear.

Excellent for a variety of packaging, bundling and repair applications.

### Main Application

- Sealing of ducts
- Fastening of protection films
- Sealing of rubbish bags
- Fixing, closing, packaging and a lot more!

### Technical Data

■ Backing material	PE laminated cloth	■ Elongation at break	16 %
■ Total thickness	190 µm 7.5 mils	■ Tensile strength	39 N/cm 22.3 lbs/in
■ Type of adhesive	natural rubber	■ Temperature resistance (30 min)	93 °C 199 °F
■ Adhesion to steel	4.95 N/cm 45.2 oz/in	■ Mesh	27 count per square inch

### Properties

■ Hand tearability	+	■ Water resistance	o
■ Straight tear edges	+		

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

For latest information on this product please visit <http://l.tesa.com/?ip=64613>

Page 1 of 1 / As of 10/23/14

#### tesa tape, inc.

5825 Carnegie Boulevard  
Charlotte, NC 28209  
Phone: 704 554 0707  
Toll Free: 800 426 2181  
Fax: 800 852 8831  
customer@tesatape.com

[www.tesatape.com](http://www.tesatape.com)

#### Technical Tape México S.A. de C.V.

Av. Santa Fe No. 170  
German Centre P 6-3-3Col.  
Lomas de Santa Fe  
Mexico D.F. C.P. 01210  
Phone: +52 (55) 5292 6978  
Fax: +52 (55) 5292 6977

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.