

tesa® 53311

High-Performance Strength Fiberglass Reinforced Filament Tape

PRODUCT INFORMATION

Product Description

tesa® 53311 is a very high strength polyester backed fiberglass reinforced filament tape.
tesa® 53311 has an aggressive and high shear resistant adhesive system.

Main Application

- Pallet securing
- Bundling of very heavy goods
- Closure and reinforcement of very heavy cartons
- Securing of coils

Technical Data

■ Backing material	PET-fiber & BOPP	■ Adhesion to steel	4.37 N/cm
■ Total thickness	175 µm	■ Elongation at break	39.9 oz/in
	6.9 mils	■ Tensile strength	4 %
■ Type of adhesive	natural rubber		437.8 N/cm
			250 lbs/in

For latest information on this product please visit <http://l.tesa.com/?ip=53311>

Page 1 of 1 / As of 09/12/14

tesa tape, inc.

5825 Carnegie Boulevard
Charlotte, NC 28209
Phone: 704 554 0707
Toll Free: 800 426 2181
Fax: 800 852 8831
customer care@tesatape.com

<http://www.tesatape.com>

Technical Tape México S.A. de C.V.

Av. Santa Fe No. 170
German Centre P 6-3-3Col.
Lomas de Santa Fe
Mexico D.F. C.P. 01210
Phone: +52 (55) 5292 6978
Fax: +52 (55) 5292 6977

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.