

tesa® 53302

Premium Kraft Flatback Tape, Natural Rubber Adhesive

PRODUCT INFORMATION

Product Description

A moisture-resistant flatback tape with an aggressive natural/synthetic rubber pressure-sensitive adhesive. This tape is designed to offer a positive, attractive seal and excellent adhesion to minimize carton sealing failures and prevent pilferage. This product has an excellent balance of machine and cross-direction tensile and tear strength. Excellent for many splicing needs. Available Colors: Tan

Main Application

- Carton Sealing
- Packaging
- Silk Screening
- · Picture Framing
- Beaming/Leasing
- Splicing
- Tabbing

Technical Data

Backing material

paper

Adhesion to steel

4.7 N/cm

Total thickness

180 µm 7.1 mils

Elongation at break

42.9 oz/in 7 %

Type of adhesive

natural & synthetic rubber Tensile strength

63 N/cm 36 lbs/in

For latest information on this product please visit http://l.tesa.com/?ip=53302

Page 1 of 1 / As of 09/12/14

tesa tape, inc.

5825 Carnegie Boulevard Charlotte, NC 28209 Phone: 704 554 0707 Toll Free: 800 426 2181 Fax: 800 852 8831 customercare@tesatape.com

México S.A. de C.V. Av. Santa Fe No. 170 German Centre P 6-3-3Col. Lomas de Santa Fe Mexico D.F. C.P. 01210 Phone: +52 (55) 5292 6978

Fax: +52 (55) 5292 6977

Technical Tape

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.