NOPI™ 53327

General-Purpose Fiberglass Reinforced Filament Tape

PRODUCT INFORMATION

Product Description

NOPI™ 53327 is a low tensile, economical fiberglass filament tape with an aggressive, high shear resistant adhesive system. Available Colors: Transparent

Main Application

- Used for palletizing and unitizing corrugated and paper board boxes
- Non-critical bundling applications

Technical Data

Backing material	glassfiber & BOPP	Adhesion to steel	7.6 N/cm 69.4 oz/in
Total thickness	96.52 µm 3.8 mils	Elongation at break	4.5 %
Type of adhesive	synthetic rubber	Tensile strength	175 N/cm 99.9 lbs/in

For latest information on this product please visit http://l.tesa.com/?ip=53327

tesa tape, inc.

5825 Carnegie Boulevard
Charlotte, NC 28209
Phone: 704 554 0707
Toll Free: 800 426 2181
Fax: 800 852 8831
customercare@tesatape.com

http://www.tesatape.com

Technical Tape México S.A. de C.V.

Av. Santa Fe No. 170
German Centre P 6-3-3Col.
Lomas de Santa Fe
Mexico D.F. C.P. 01210
Phone: +52 (55) 5292 6978
Fax: +52 (55) 5292 6977

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.