

tesa® 50533

High adhesion temporary protection tape for freshly painted surfaces

PRODUCT INFORMATION

Product Description

tesa® 50533 consists of a UV-stabilized backing coated with a high adhesion EVA adhesive.

User benefits:

- Preserves the paint finish for up to 6 months of outdoor storage
- Perfect adhesive to the range of the paint finish, even during transportation (tested at speeds higher than 160 km/h – 100 mph)
- Easy disposal - both the film and the adhesive systems are environmentally friendly

Main Application

- 50533 effectively provides peeling off protection for filmic systems like tesa® 50530, especially in uniquely shaped areas, and prevents infiltration by dust and humidity
- tesa® 50533 is suitable for die-cutting and can be printed to be used as security, steering or marking label
- 50533 can also be used as base material for heavy duty protection pads for bumpers and door edges

Automotive Temporary Surface Protection

Technical Data

■ Backing material	polyolefinic film	■ Elongation at break	660 %
■ Total thickness	96 µm 3.8 mils	■ Tensile strength	21.5 N/cm 12.3 lbs/in
■ Type of adhesive	EVA	■ UV-resistance	52 weeks
■ Adhesion to steel	3 N/cm 27.4 oz/in		

Properties

■ Easy to remove	yes	■ Paint compatibility	++
■ Suitable for die cutting	yes	■ Resistance to chemicals	++

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

Additional Info

tesa® Edge Securing 50533 is also available as die cut product solution as tesa® Edge Securing 54533.

For latest information on this product please visit <http://l.tesa.com/?ip=50533>

Page 1 of 1 / As of 11/01/14

tesa tape, inc.

5825 Carnegie Boulevard
Charlotte, NC 28209
Phone: 704 554 0707
Toll Free: 800 426 2181
Fax: 800 852 8831
customercare@tesatape.com

www.tesatape.com

Technical Tape México S.A. de C.V.

Av. Santa Fe No. 170
German Centre P 6-3-3Col.
Lomas de Santa Fe
Mexico D.F. C.P. 01210
Phone: +52 (55) 5292 6978
Fax: +52 (55) 5292 6977

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.