

**PRODUCTION GRADE, DIRECTLY PRINTABLE
FIBERGLASS REINFORCED BOPP PACKAGING TAPE**

TYPICAL APPLICATIONS

- For use on Siat L33, L35, L233 (or equivalent) surface printing presses

ADVANTAGES AND BENEFITS

- Directly printable with all leading brands of solvent inks
- Exclusive release coat technology allowing for consistent unwind and faster drying times - resulting in more efficient use of machines
- Superior ink anchorage without pickoff
- Quiet off the roll

CONSTRUCTION

Overall Grade/Function: Production
 Backing: Directly printable, fiberglass reinforced, biaxially oriented polypropylene film
 Adhesive: Hot melt, synthetic rubber



COLOR(S)

Clear (CLR)

STANDARD WIDTH(S) **STANDARD LENGTH(S)**
 144 mm 330 m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	100 lbs/in width	175.1 N/10 mm
Adhesion to Stainless Steel	73 oz/in width	7.99 N/10 mm
Thickness	4.5 mils	0.11 mm
Elongation	3.7%	3.7%
Service Temperature Range	-10 F to 150 F	-23 C to 66 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

*Shurtape® is a registered trademark of Shurtape Technologies, LLC
 Form# TDS-GS496- 06/16/2014