



Revision date : 4-2-2010  
Print date : 18-3-2010

**SAFETY DATA SHEET**  
according to Regulation (EC) No 1907/2006

**1. IDENTIFICATION OF THE PREPARATION AND OF THE COMPANY**

1.1. Identification of the preparation :

- Product Name : Mastinox 6856K Jointing Compound
- Product identification : 1102XXXX

1.2. Use of the preparation :

- Sealant


1.3. Company identification :

PPG Coatings Manufacturing SARL  
7, Allée de la Plaine  
76700 Gonfreville l'Orcher  
France

- Technical contact : Aerospace Laboratory
- Tel : +33 (0)2 35 53 54 35
- Fax : +33 (0)2 35 53 54 36
- e-mail address : EurMsdsContact@ppg.com

1.4. Emergency telephone :

- Company emergency telephone number : +33 (0)2 35 53 43 50



**2. HAZARDS IDENTIFICATION**

- F - T - N - HIGHLY FLAMMABLE - TOXIC - DANGEROUS FOR THE ENVIRONMENT
- May cause cancer.
- Harmful by inhalation, in contact with skin and if swallowed.
- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

Chemical family : Polyester

Substances presenting a health or environmental hazard within the meaning of the Dangerous Substances Directive 67/548/EC and amendments.  
For the hazards of the preparation, see Section 2.

SUBSTANCES % by wt in the product	SYMBOL and R(*) phrases of the pure substances	CAS number	EINECS / ELINCS
METHYLCYCLOHEXANE 0.1 - < 0.2 %	Xn N F R65,R38,R67,R51/53,R11	108-87-2	203-624-3
HEPTANE 0.1 - < 0.2 %	Xn N F R65,R38,R67,R50/53,R11	142-82-5	205-563-8
OCTANE 0.2 - < 0.5 %	Xn N F R65,R38,R67,R50/53,R11	111-65-9	203-892-1
ETHYLBENZENE 1 - < 2 %	Xn F R20,R11	100-41-4	202-849-4
SILICA: AMORPHOUS; FUMED 2 - < 3 %		112945-52-5	231-545-4
TOLUENE 3 - < 5 %	Xn F R63,R48/20,R65,R38,R67,R11	108-88-3	203-625-9
BARYUM CHROMATE (BA%) 5 - < 7 %	Xn R20/22	10294-40-3	233-660-5
XYLENE (MIXTURE OF ISOMERS) 5 - < 7 %	Xn R20/21,R38,R10	1330-20-7	215-535-7
STRONTIUM CHROMATE 12.5 - < 15 %	T N R45,R22,R50/53	7789-06-2	232-142-6

(\*) See full text of phrases under Section 16.

#### 4. FIRST AID MEASURES

**General :**

In all cases of doubt or when symptoms persist, seek medical attention. Have Safety Data Sheet information available. Never give anything by mouth to an unconscious person.

**Inhalation :**

Remove to fresh air, keep patient warm and at rest. If breathing has stopped, administer artificial respiration. Give nothing by mouth. If unconscious, place in recovery position and seek medical advice.

**Eye contact :**

Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart, and seek medical advice.

**Skin contact :**

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognized skin cleaners. Do NOT use solvents or thinners.

**Ingestion :**

If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

#### 5. FIRE-FIGHTING MEASURES

**Extinguishing media :**

- Recommended: universal resistant foam, CO2, powder.
- Not to be used: water jet.

**Recommendations :**

- Fire will produce dense black smoke. Exposure to decomposition products may cause a Health Hazard. Fire fighters should wear self-contained breathing apparatus.
- Water mist may be used to cool closed containers to prevent pressure build-up and possible auto-ignition and explosion when exposed to extreme heat.
- Do not weld, expose to extreme heat or ignition sources, empty containers which have contained flammable products.

.../..

- Do not allow run-off from fire fighting to enter drains or water courses.

## 6. ACCIDENTAL RELEASE MEASURES

- Exclude sources of ignition and ventilate the area. Avoid breathing vapours by using appropriate respiratory protective equipment. Refer to protective measures listed in sections 7 & 8.
- Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal in accordance with local regulations (see section 13). Do not allow to enter drains or watercourses.
- Clean preferably with a detergent ; avoid use of solvents.
- If the product contaminates lakes, rivers or sewers, inform water authorities in accordance with local regulations.

## 7. HANDLING AND STORAGE

### 7.1 Handling

- Smoking, eating and drinking should be prohibited during handling.
- Keep container tightly closed. Any containers which are open should be carefully resealed.
- Avoid skin and eye contact. Avoid inhalation of vapour and spray mist.
- An eye wash station and safety shower should be in close proximity within the area of use.

#### Packaging materials :

- Recommended : keep preferably in original container.
- Avoid :
  - \* Those sensitive to solvents

- Handle and open containers with care to avoid sudden ejections. Never use pressure to empty : container is not a pressure vessel. Clean or discard contaminated clothing and shoes.
- Preparation may charge electrostatically : always use earthing leads when transferring between containers. Operators should wear antistatic footwear and clothing, and floors should be electrically conductive.
- Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air, and avoid vapour concentration higher than the Occupational Exposure Limits.
- Additionally, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Isolate from sources of heat, sparks and open flame. Non-sparking tools should be used.
- Avoid the inhalation of dust particulates and spray mist arising from the application of this strontium chromate containing preparation. Also avoid the inhalation of dust, particulates, and fumes from the treatment of surfaces coated with this preparation by dry sanding or hot working (welding, brazing, cutting, etc ...). Wet sanding methods should be favoured.

### 7.2 Storage

The product is hygroscopic and should be stored in a dry area.

For flash points below 23 °C store in accordance with the Petroleum (Mixtures) Order SRO 1929 No. 993.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1 Engineering measures

..1.

Avoid the inhalation of vapour, spray mist and particulates. This should be achieved by the provision of local exhaust ventilation and good general extraction to keep air-borne concentration below the Occupational Exposure Limits (OEL). If these are not sufficient to comply with OEL, suitable respiratory protection must be worn.

## 8.2 Exposure limits

Substances	----- Workplace Exposure limit (-----)				Comments
	ppm	8-hr limit mg/m3	ppm	15-minute limit mg/m3	
BARYUM CHROMATE (BA%)	Cr	0.05	-	-	Carc Sen
XYLENE (MIXTURE OF ISOMERS)	50	220	100	441	Sx
TOLUENE	50	191	100	384	Sx
ETHYLBENZENE	100	441	125	552	Sx
STRONTIUM CHROMATE	Cr	0.05	-	-	Carc Sen
HEPTANE	500	-	-	-	
SILICA, AMORPHOUS, FUMED	-	2.4	-	-	RD

( ) : See Guidance Note EH 40, Workplace exposure limits  
 Carc : Capable of causing cancer  
 Sk : Can be absorbed through skin  
 Sen : Capable of causing occupational asthma  
 RD : Respirable dust  
 - : Not estimated

## 8.3 Personal protection

All Personal Protective Equipment, including Respiratory Protective Equipment, used to control exposure to hazardous substances must be selected to meet the requirements of the COSHH Regulations.

### Respiratory protection :

Appropriate certified respiratory protective equipment should be selected according to the type of contaminants, following official and manufacturers instructions including proper fitting.

### Hand protection :

For prolonged or repeated contact, we recommend gloves type : polyvinyl alcohol, nitrile rubber, neoprene rubber.

Barrier creams may help to protect exposed areas of the skin. However, they should not be applied once exposure has occurred.

### Eye protection :

Use safety glasses to protect against splashes.

### Skin protection :

Personnel should wear protective clothing made of antistatic and fire resistant fibres. All parts of the body should be washed after contact.

Use good hygiene and industrial practices, keeping working clothes clean.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state at 20°C : Liquid
- Flash point : 12°C Method : ISO 3679
- Specific gravity at 20°C : 1.5 g/cm<sup>3</sup> Method : ISO 2811

..

- Vapour density : > air
- Lower explosion limit ( vol %) : 1.0 (ETHYLBENZENE)
- Upper explosion limit ( vol %) : 7.0 (TOLUENE)
- Miscibility in water at 20°C : not miscible
- pH : not applicable
- Percent volatile by weight : 13.0      by volume : 22.0
- Vapour pressure at 20°C : 14 mm Hg

## 10. STABILITY AND REACTIVITY

Stable under recommended storage and handling conditions (see section 7).  
In case of combustion, may produce hazardous decomposition products such as :

- Carbon monoxide
- Oxides of Chromium

## 11. TOXICOLOGICAL INFORMATION

There are no data available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See Sections 3 and 15 for details.

Exposure to component solvents vapours at concentrations in excess of the stated Occupational Exposure Limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness, and in extreme cases loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic dermatitis and absorption through the skin.  
The liquid splashed in the eyes may cause irritation and reversible damage.

The preparation contains strontium chromate which can increase the risk of human cancer after a long-term exposure to high levels of this chromate.

## 12. ECOLOGICAL INFORMATION

There is no data available on the preparation itself.  
The product should not be allowed to enter drains or water courses.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is classified for eco-toxicological properties accordingly. See Sections 3 and 15 for details.

## 13. DISPOSAL CONSIDERATIONS

The provisions of Council Directive 91/689/EEC and subsequent Amendments and Decisions apply to wastes from the product as supplied.

Hazardous Properties :  
H14 Ecotoxic  
H3-A Highly flammable  
H6 Toxic  
H7 Carcinogenic

Do not allow into drains or water courses.  
Waste and emptied containers must be disposed in accordance with :  
- Control of Pollution Act 1974,

.. /..

- Special Waste Regulations 1996,
  - Duty of Care Regulations 1992.
- They should be recycled or disposed of through a licenced waste management facility.

#### 14. TRANSPORT INFORMATION

UN Number: UN1263  
Proper Shipping Name: Paint  
Technical Name: None  
Hazard Class: 3  
Subsidiary Class: None  
Packing Group:II

ADR/RID  
Tunnel Code: D / E



IMDG  
EMS No.: F-E-S-E  
Marine Pollutant: Octane; Strontium Chromate

ICAO/IATA  
Passenger Air Packing Instruction: 305  
Passenger Air Quantity/Package: 5 Liters  
Cargo Air Packing Instruction: 307  
Cargo Air Quantity/Package: 60 Liters

#### 15. REGULATORY INFORMATION

##### LABEL

According to the Directive (1999/45/EC), relating to the classification packaging and labelling of dangerous substances and preparations, the product is labelled as follows :



- F - T - N - HIGHLY FLAMMABLE - TOXIC - DANGEROUS FOR THE ENVIRONMENT
- CONTAINS : BARYUM CHROMATE (BA%), STRONTIUM CHROMATE
- RESTRICTED TO PROFESSIONAL USERS.
- R45 May cause cancer.
- R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- S45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
- S53 Avoid exposure - obtain special instructions before use.
- S16 Keep away from sources of ignition - No smoking.
- S51 Use only in well-ventilated areas.
- S36/37 Wear suitable protective clothing and gloves.
- S61 Avoid release to the environment. Refer to special instructions/ Safety data sheets.

## 16. OTHER INFORMATION

Full text of R phrases with N° appearing in Section 3:

- R65 Harmful; may cause lung damage if swallowed.
- R38 Irritating to skin.
- R67 Vapours may cause drowsiness and dizziness.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R11 HIGHLY FLAMMABLE.
- R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R20 Harmful by inhalation.
- R63 Possible risk of harm to the unborn child.
- R48/20 Harmful : danger of serious damage to health by prolonged exposure through inhalation.
- R20/22 Harmful by inhalation and if swallowed.
- R20/21 Harmful by inhalation and in contact with skin.
- R10 FLAMMABLE.
- R45 May cause cancer.
- R22 Harmful if swallowed.

The information contained in this data sheet is based on present scientific and technical knowledge. AS OF : 4-2-2010

The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

- The information contained in this Safety Data Sheet is provided in accordance with the requirements of the Chemicals (Hazard Information and Packaging) Regulations.
- The provision of the Health and Safety at Work Act and the Control of Substances Hazardous to Health Regulations apply to the use of this product at work.

END OF SAFETY DATA SHEET