


5068

Polyethylene Greenhouse Patch Tape



Backing: LDPE Film

Adhesive: Acrylic (A100)

Liner: N/A

Colors: Clear

Specifications: N/A

Size Options: Incremental widths 1/4" - 54" x 108ft

Applications

- Patching and seaming of greenhouse films
- General purpose sealing, splicing, and patching

• Temporary hold down

Features	Benefits
----------	----------

LDPE Film	Conforms well to irregular surfaces
	Withstandsshort-term exposure to the elements
	Excellent moisture barrier
	Optically clear and hand tearable
Acrylic Adhesive	High adhesion and cohesion
	 Excellent all temperature performance
	Excellent long-term stability

Typical Test Values

	Standard	Standard UOM Metric UOM		ЮМ	Test Method
Total Thickness	5.5	mils	0.140	mm	PSTC-133
Substrate Thickness	4.5	mils	0.114	mm	PSTC-133
Adhesion to Steel	50	oz/in	5.47	N/cm	ASTM D-3330
Tensile Strength	11	lb/in	19.26	N/cm	ASTM D-3759
Elongation	400%				
Application Temperature	50 to 120 °F		10 to 49 °C		
Operating Temperature	-40 to 190 °F		-40 to 8	8 °C	

Recommended Storage Conditions: 40-60% Humidity, 60-80% Standard Shelf Life (at 25%): 12 months from shipment date

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY GLOBAL'S knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.

