


## **Premium Preservation & Sealing Tape**



**Backing:** UV Stabilized LDPE Film

**Adhesive:** Urethane (U514)

Liner: N/A
Colors: White
Specifications: N/A

**Size Options:** Incremental widths 1/4" - 48" x 108ft

## **Applications**

- Long-term preservation, sealing, and splicing
- Direct protective mask on aircraft, trucks, boats, or industrial equipment during outdoor storage
- Splicing, seaming, and sealing polyethylene films
- Used in conjunction with outdoor shrink film to secure film and seal film edges during transport or extended outdoor storage

## Features Benefits

	20.10113
LDPE Film	Excellent chemical and solvent resistance
	Highly conformable
	Stands up to extreme environmental conditions
	Moisture resistant
Urethane Adhesive	Aggressive bond
	<ul> <li>Controlled unwind</li> </ul>
	<ul> <li>Easy to apply even at wide widths</li> </ul>
	Will not lift or flag
	<ul> <li>Excellent low-temperature adhesion</li> </ul>

## **Typical Test Values**

	Standard UOM		Metric UOM		Test Method
Total Thickness	10.5	mils	0.267	mm	PSTC-133
Substrate Thickness	7.5	mils	0.191	mm	PSTC-133
Adhesion to Steel	65	oz/in	7.11	N/cm	ASTM D-3330
Tensile Strength	18	lb/in	31.52	N/cm	ASTM D-3759
Elongation	650%				
Application Temperature	50 to 120 °F		10 to 49 °C		
Operating Temperature	-40 to 200 °F		-40 to 93 °C		

Recommended Storage Conditions: 40-60% Humidity, 60-80% Standard Shelf Life (at 25%C): 12 months from shipment date

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY GLOBAL'S knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.

