


AST500

Automotive SealTite Tape



Backing: UV Resistant LDPE Film

Adhesive: Rubber (R418)

Liner: N/A

Colors: White

Specifications: N/A

Size Options: Incremental widths 1/4" - 48" x 108ft

Applications

 Ideal for securing and wrapping shrink film and standard polyethylene sheeting to various automotive surfaces Bonds to glass, painted metal, and plastic trim to protect surfaces during storage and transport

Features Benefits

LDPE Film	Conformable and hand tearable
	Abrasion resistant
	 UV and weather resistant - up to 6 months
	 Moisture, solvent, and chemical resistant
Rubber Adhesive	Good quick stick
	 Excellent adhesion to PE and shrink film
	 Repostionable
	 Clean removal from most surfaces
	 Excellent low-temperature adhesion

Typical Test Values

		<u> </u>			Test Method	
	Standard UOM		Metric UOM			
Total Thickness	9.0	mils	0.229	mm	PSTC-133	
Substrate Thickness	7.5	mils	0.191	mm	PSTC-133	
Adhesion to Steel	24	oz/in	2.63	N/cm	ASTM D-3330	
Tensile Strength	15	lb/in	26.27	N/cm	ASTM D-3759	
Elongation	500%					
Application Temperature	50 to 120 °F		10 to 49 °C			
Operating Temperature	-40 to 180 °F		-40 to 82 °C			

Recommended Storage Conditions: 40-60% Humidity, 60°F-80°F

Standard Shelf Life (at 25C): 12 months from shipment date

The information presented netern'was prepared at better transitions core furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal

