

# **Safety Data Sheet**

Copyright,2018,3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 10-8338-5
 Version Number:
 18.02

 Issue Date:
 01/18/18
 Supercedes Date:
 03/06/17

# **SECTION 1: Identification**

### 1.1. Product identifier

INTERAM(tm) I-10A and I-10 MATS

### **Product Identification Numbers**

98-0400-0229-1, 98-0400-0506-2, 98-0400-0507-0

# 1.2. Recommended use and restrictions on use

### Recommended use

Fire Protection

### 1.3. Supplier's details

MANUFACTURER: 3M

DIVISION: Industrial Adhesives and Tapes Division
ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA
Telephone: 1-888-3M HELPS (1-888-364-3577)

### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

# **SECTION 2: Hazard identification**

### 2.1. Hazard classification

Carcinogenicity: Category 2.

### 2.2. Label elements

Signal word

Warning

#### **Symbols**

Health Hazard |

# **Pictograms**

Page 1 of 9



### **Hazard Statements**

Suspected of causing cancer by inhalation.

### **Precautionary Statements**

### **Prevention:**

Do not handle until all safety precautions have been read and understood.

Do not breathe dust.

Use personal protective equipment as required.

#### **Response:**

IF exposed or concerned: Get medical advice/attention.

#### Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

24% of the mixture consists of ingredients of unknown acute oral toxicity.

# **SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
Vermiculite	1318-00-9	30 - 60 Trade Secret *
Refractory Ceramic Fibers (RCF)	142844-00-6	15 - 40 Trade Secret *
Insulation NJTS Reg. No. 04499600-7212	Trade Secret*	10 - 30 Trade Secret *
Polymer NJTS Reg. No. 04499600-7269	Trade Secret*	5 - 10 Trade Secret *
Aluminum	7429-90-5	0 - 5 Trade Secret *

NJTS or NJTSRN: New Jersey Trade Secret Registry Number.

# **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

#### **Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

# **Skin Contact:**

Wash with soap and water. If signs/symptoms develop, get medical attention.

### **Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

Page 2 of 9

<sup>\*</sup>The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

#### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

### 5.1. Suitable extinguishing media

Material will not burn. Use a fire fighting agent suitable for the surrounding fire.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### 5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

# **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

#### 6.2. Environmental precautions

Avoid release to the environment.

# 6.3. Methods and material for containment and cleaning up

Collect spilled material using a vacuum cleaner with a High Efficiency Particulate Air (HEPA) filter. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

For industrial or professional use only. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Use personal protective equipment (gloves, respirators, etc.) as required.

### 7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

# **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	<b>Additional Comments</b>
CERAMIC FIBERS	142844-00-	ACGIH	TWA(as fiber):0.2 fiber/cc	A2: Suspected human
	6			carcin.

Page 3 of 9

Aluminum	7429-90-5	ACGIH	TWA(respirable fraction):1	A4: Not class. as human
			mg/m3	carcin
Aluminum	7429-90-5	OSHA	TWA(as Al total dust):15	
			mg/m3;TWA(as Al, respirable	
			fraction):5 mg/m3	
DUST, INERT OR NUISANCE	7429-90-5	OSHA	TWA(as total dust):15	
			mg/m3;TWA(as total dust):50	
			millions of particles/cu. ft.(15	
			mg/m3);TWA(respirable	
			fraction):15 millions of	
			particles/cu. ft.(5	
			mg/m3);TWA(respirable	
			fraction):5 mg/m3	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

# Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

# Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

# **SECTION 9: Physical and chemical properties**

# **9.1. Information on basic physical and chemical properties General Physical Form:**Solid

Page 4 of

Odor, Color, Grade: Odorless, gray mat with/without aluminum

**Odor threshold** Not Applicable pН Not Applicable Melting point No Data Available **Boiling Point** Not Applicable **Flash Point** Not Applicable **Evaporation rate** Not Applicable Not Classified Flammability (solid, gas) Flammable Limits(LEL) Not Applicable Flammable Limits(UEL) Not Applicable Not Applicable Vapor Pressure

Vapor DensityNot ApplicableDensity0.625 g/ml [@ 20 °C]Specific Gravity0.625 [Ref Std:WATER=1]

Solubility in Water Nil

Solubility- non-water Not Applicable Partition coefficient: n-octanol/ water No Data Available **Autoignition temperature** Not Applicable **Decomposition temperature** Not Applicable Not Applicable Viscosity Molecular weight No Data Available **Volatile Organic Compounds** Not Applicable Percent volatile Not Applicable **VOC Less H2O & Exempt Solvents** Not Applicable

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

None known.

# 10.5. Incompatible materials

None known.

### 10.6. Hazardous decomposition products

SubstanceConditionHydrocarbonsNot SpecifiedCarbon monoxideNot SpecifiedCarbon dioxideNot Specified

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be

Page 5 of 9

reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### **Inhalation:**

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

#### **Skin Contact:**

Mechanical Skin irritation: Signs/symptoms may include abrasion, redness, pain, and itching.

#### **Eye Contact:**

Mechanical eye irritation: Signs/symptoms may include pain, redness, tearing and corneal abrasion.

### **Ingestion:**

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

### **Additional Health Effects:**

### Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
Generic: CERAMIC FIBERS	142844-00-6	Anticipated human carcinogen	National Toxicology Program Carcinogens
Generic: GLASS FILAMENTS	142844-00-6	Anticipated human carcinogen	National Toxicology Program Carcinogens
Refractory Ceramic Fibers (RCF)	142844-00-6	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

## **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

# **Acute Toxicity**

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE2,000 - 5,000 mg/kg
Vermiculite	Dermal		LD50 estimated to be > 5,000 mg/kg
Vermiculite	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Refractory Ceramic Fibers (RCF)	Dermal		LD50 estimated to be > 5,000 mg/kg
Refractory Ceramic Fibers (RCF)	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Aluminum	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminum	Ingestion		LD50 estimated to be > 5,000 mg/kg
Aluminum	Inhalation-	Rat	LC50 > 0.888 mg/l
	Dust/Mist		
	(4 hours)		

ATE = acute toxicity estimate

### Skin Corrosion/Irritation

Name Species Value
--------------------

Page 6 of 9

INTERAM(tm) I-10A and I-10 MATS	01/18/18	
---------------------------------	----------	--

Vermiculite	Professio	No significant irritation
	nal	
	judgeme	
	nt	
Aluminum	Rabbit	No significant irritation

**Serious Eye Damage/Irritation** 

Name	Species	Value
Vermiculite	Professio	No significant irritation
	nal	
	judgeme	
	nt	
Aluminum	Rabbit	No significant irritation

# **Skin Sensitization**

Name	Species	Value
Aluminum	Guinea	Not classified
	pig	

**Respiratory Sensitization** 

Name	Species	Value
Aluminum	Human	Not classified

**Germ Cell Mutagenicity** 

Name	Route	Value
Aluminum	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Refractory Ceramic Fibers (RCF)	Inhalation	Multiple	Carcinogenic
		animal	
		species	

# Reproductive Toxicity

# Reproductive and/or Developmental Effects

For the component/components, either no data are currently available or the data are not sufficient for classification.

# Target Organ(s)

# **Specific Target Organ Toxicity - single exposure**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Specific Tunger organi Tomony Telebrate and Source						
Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure
						Duration
Refractory Ceramic Fibers	Inhalation	pulmonary fibrosis	Not classified	Rat	NOAEL 36	12 months
(RCF)					fibers/cc	
Refractory Ceramic Fibers	Inhalation	heart   liver   kidney	Not classified	Rat	NOAEL 187	18 months
(RCF)		and/or bladder			fibers/cc	
Aluminum	Inhalation	nervous system	Not classified	Human	NOAEL Not	occupational
		respiratory system			available	exposure

# **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

### **Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

### **Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

# **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility.

EPA Hazardous Waste Number (RCRA): Not regulated

# **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

# **SECTION 15: Regulatory information**

### 15.1. US Federal Regulations

Contact 3M for more information.

### **EPCRA 311/312 Hazard Classifications:**

### Physical Hazards

Not applicable

### Health Hazards

Carcinogenicity

### Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	% by Wt		
Aluminum	7429-90-5	Trade Secret	0 -	5
Aluminum (Aluminum)	7429-90-5	0 - 5		

### 15.2. State Regulations

Contact 3M for more information.

### 15.3. Chemical Inventories

Contact 3M for more information.

Page 8 of

INTERAM(tm) I-10A and I-10 MATS

01/18/18

#### 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

# **SECTION 16: Other information**

NFPA Hazard Classification

Health: 1 Flammability: 0 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

 Document Group:
 10-8338-5
 Version Number:
 18.02

 Issue Date:
 01/18/18
 Supercedes Date:
 03/06/17

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued.3MMAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3Mproduct is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3Mproduct, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3Mproduct to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3Mprovides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information,3Mmakes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from3M

3M USA SDSs are available at www.3M.com

Page 9 of 9