

Safety Data Sheet

Copyright, 2023, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 32-6787-9
 Version Number:
 4.02

 Issue Date:
 01/18/23
 Supercedes Date:
 09/10/21

SECTION 1: Identification

1.1. Product identifier

3MTM Scotch-WeldTM Threadlocker TL43, Blue

Product Identification Numbers

62-3428-1060-3, 62-3428-1065-2, 62-3428-3960-2, 62-3428-5060-9, 62-3428-8360-0 7100039223, 7100039219, 7100039220, 7100039221, 7100039222

1.2. Recommended use and restrictions on use

Recommended use

Adhesive

1.3. Supplier's details

MANUFACTURER: 3M

DIVISION: Industrial Adhesives and Tapes Division **ADDRESS:** 3M Center, St. Paul, MN 55144-1000, USA

Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2A. Skin Corrosion/Irritation: Category 2.

Skin Sensitizer: Category 1. Carcinogenicity: Category 1B.

Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Exclamation mark | Health Hazard |

Pictograms





Hazard Statements

Causes serious eye irritation.

Causes skin irritation.

May cause an allergic skin reaction.

May cause cancer.

Causes damage to organs through prolonged or repeated exposure:

nervous system

respiratory system

Precautionary Statements

Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves and eye/face protection.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF exposed or concerned: Get medical advice/attention.

Storage:

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Triethylene Glycol Dimethacrylate	109-16-0	30 - 60 Trade Secret *
Diisopropylnaphthalene	38640-62-9	20 - 40 Trade Secret *
Amorphous Silica	68909-20-6	1 - 10 Trade Secret *
Hydroxypropyl Methacrylate	27813-02-1	1 - 10 Trade Secret *
Polyester Resin (NJTS Reg. No. 04499600-7087)	Trade Secret*	1 - 10 Trade Secret *
Silica	67762-90-7	1 - 5 Trade Secret *
Cumene Hydroperoxide	80-15-9	< 2 Trade Secret *
Saccharin	81-07-2	<= 2 Trade Secret *
2,2'-(P-Tolylimino)diethanol	3077-12-1	< 1 Trade Secret *

Page 2 of 15

Acrylic Acid	79-10-7	< 1 Trade Secret *
Ethylene Glycol	107-21-1	< 1 Trade Secret *
Naphthalene, (1-methylethyl)-	29253-36-9	< 1 Trade Secret *
1-Acetyl-2-Phenylhydrazine	114-83-0	<= 0.7 Trade Secret *
2,6-di-tert-Butyl-p-cresol	128-37-0	<= 0.5 Trade Secret *
N,N-Dimethyl-p-toluidine	99-97-8	<= 0.5 Trade Secret *
Titanium Dioxide	13463-67-7	<= 0.1 Trade Secret *

NJTS or NJTSRN: New Jersey Trade Secret Registry Number.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eve Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Oxides of Nitrogen	During Combustion
Oxides of Sulfur	During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

^{*}The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Protect from sunlight. Store away from heat. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Ethylene Glycol	107-21-1	ACGIH	TWA(Vapor fraction):25	A4: Not class. as human
			ppm;STEL(Vapor fraction):50	carcin
			ppm;STEL(Inhalable	
			aerosol):10 mg/m3	
2,6-di-tert-Butyl-p-cresol	128-37-0	ACGIH	TWA(inhalable fraction and	A4: Not class. as human
			vapor):2 mg/m3	carcin
Titanium Dioxide	13463-67-7	ACGIH	TWA(Respirable nanoscale	A3: Confirmed animal
			particles):0.2	carcin.
			mg/m3;TWA(Respirable	
			finescale particles):2.5 mg/m3	
Titanium Dioxide	13463-67-7	OSHA	TWA(as total dust):15 mg/m3	
SILICA, AMORPHOUS	67762-90-7	OSHA	TWA:20 millions of	
			particles/cu. ft.;TWA	

			concentration:0.8 mg/m3	
SILICA, AMORPHOUS	68909-20-6	OSHA	TWA:20 millions of	
			particles/cu. ft.;TWA	
			concentration:0.8 mg/m3	
Acrylic Acid	79-10-7	ACGIH	TWA:2 ppm	A4: Not class. as human
				carcin, Danger of
				cutaneous absorption
Cumene Hydroperoxide	80-15-9	AIHA	TWA:6 mg/m3(1 ppm)	SKIN
N,N-Dimethyl-p-toluidine	99-97-8	AIHA	TWA:0.5 ppm	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical stateLiquidColorBlue

Specific Physical Form: Thixotropic Liquid

Odor Mild Odor

Odor thresholdNo Data AvailablepHNot ApplicableMelting pointNot Applicable

Boiling Point >=300 °F [@ 760 mmHg]

Flash Point >=212 °F [Test Method: Tagliabue Closed Cup]

Evaporation rateNegligibleFlammability (solid, gas)Not ApplicableFlammable Limits(LEL)No Data AvailableFlammable Limits(UEL)No Data AvailableVapor Pressure<=5 mmHg</th>

 Vapor Density
 1.01 [Ref Std:AIR=1]

 Density
 1.1 - 1.15 g/ml [@, 20 °C]

Specific Gravity 1.1 - 1.15 [@ 20 °C] [*Ref Std*: WATER=1]

Solubility in WaterNegligibleSolubility- non-waterNo Data AvailablePartition coefficient: n-octanol/ waterNo Data AvailableAutoignition temperatureNo Data AvailableDecomposition temperatureNo Data Available

Viscosity2,500 - 4,000 centipoise [@ 20 °C]Hazardous Air Pollutants< 2 % weight [Test Method: Calculated]</th>

VOC Less H2O & Exempt Solvents < 5 g/l [Test Method:calculated SCAQMD rule 443.1]

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat Light

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

Substance Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient

classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eve Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

<u>Ingredient</u>	CAS No.	Class Description	Regulation
Dimethyl-p-toluidine	99-97-8	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Titanium dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation- Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg

Page 7 **of** 15

Triethylene Glycol Dimethacrylate	Dermal	Professio	LD50 estimated to be > 5,000 mg/kg
		nal	, , ,
		judgeme	
Taiathadana Charal Dioratha andata	T	nt D-4	LD50 10.927/k
Triethylene Glycol Dimethacrylate Diisopropylnaphthalene	Ingestion Dermal	Rat Rat	LD50 10,837 mg/kg LD50 > 4,500 mg/kg
Diisopropylnaphthalene	Inhalation-	Rat	LC50 > 5.64 mg/l
Disopropymaphtnaiene	Dust/Mist	Kat	LC30 > 3.04 llig/1
Diisopropylnaphthalene	Ingestion	Rat	LD50 4,130 mg/kg
Amorphous Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Amorphous Silica	Inhalation-	Rat	LC50 > 0.691 mg/l
	Dust/Mist		
	(4 hours)		
Amorphous Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Hydroxypropyl Methacrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
Hydroxypropyl Methacrylate	Ingestion	Rat	LD50 > 11,200 mg/kg
Saccharin	Dermal		LD50 estimated to be > 5,000 mg/kg
Saccharin	Ingestion	Mouse	LD50 17,000 mg/kg
Cumene Hydroperoxide	Dermal	Rat	LD50 500 mg/kg
Cumene Hydroperoxide	Inhalation-	Rat	LC50 1.4 mg/l
	Vapor (4		
~	hours)		X 7 7 0 4 0 4 0 4
Cumene Hydroperoxide	Ingestion	Rat	LD50 382 mg/kg
Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Silica	Inhalation- Dust/Mist	Rat	LC50 > 0.691 mg/l
	(4 hours)		
Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Acrylic Acid	Dermal	Rabbit	LD50 > 2,000 mg/kg
Acrylic Acid	Inhalation-	Rat	LC50 3.8 mg/l
Teryne Teru	Dust/Mist	Rut	Desc 3.6 mg 1
	(4 hours)		
Acrylic Acid	Ingestion	Rat	LD50 1,250 mg/kg
Ethylene Glycol	Ingestion	Human	LD50 1,600 mg/kg
Ethylene Glycol	Inhalation-	Other	LC50 estimated to be 5 - 12.5 mg/l
	Dust/Mist		
	(4 hours)		
Ethylene Glycol	Dermal	Rabbit	9,530 mg/kg
1-Acetyl-2-Phenylhydrazine	Dermal		LD50 estimated to be 200 - 1,000 mg/kg
1-Acetyl-2-Phenylhydrazine	Ingestion	Mouse	LD50 270 mg/kg
2,6-di-tert-Butyl-p-cresol	Dermal	Rat	LD50 > 2,000 mg/kg
2,6-di-tert-Butyl-p-cresol	Ingestion	Rat	LD50 > 2,930 mg/kg
N,N-Dimethyl-p-toluidine	Ingestion	Mouse	LD50 140 mg/kg
N,N-Dimethyl-p-toluidine	Dermal	Rabbit	LD50 > 2,000 mg/kg
N,N-Dimethyl-p-toluidine	Inhalation-	Rat	LC50 1.4 mg/l
	Dust/Mist		
2,2'-(P-Tolylimino)diethanol	(4 hours) Dermal	Rabbit	LD50 > 2,000 mg/kg
2,2'-(P-Tolylimino)diethanol	Ingestion	Rat	LD50 > 2,000 mg/kg LD50 959 mg/kg
Z,Z-(P-10lyllmino)dietnanol Titanium Dioxide	Dermal	Rabbit	LD50 959 mg/kg LD50 > 10,000 mg/kg
Titanium Dioxide Titanium Dioxide	Inhalation-	Rat	LC50 > 6.82 mg/l
Hamuili Dioxiuc	Dust/Mist	Kai	LC30 / 0.02 IIIg/I
	(4 hours)		
Titanium Dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg

 \overline{ATE} = acute toxicity estimate

Skin Corrosion/Irritation

Skin Corrosion/irritation		
Name	Species	Value
	_	
Triethylene Glycol Dimethacrylate	Guinea	Mild irritant
	pig	
Diisopropylnaphthalene	Rabbit	Minimal irritation
Amorphous Silica	Rabbit	No significant irritation
Hydroxypropyl Methacrylate	Rabbit	Minimal irritation

Page 8 **of** 15

Cumene Hydroperoxide	Rabbit	Corrosive
Silica	Rabbit	No significant irritation
Acrylic Acid	Rabbit	Corrosive
Ethylene Glycol	Rabbit	Minimal irritation
2,6-di-tert-Butyl-p-cresol	Human	Minimal irritation
	and	
	animal	
N,N-Dimethyl-p-toluidine	Rabbit	No significant irritation
2,2'-(P-Tolylimino)diethanol	Rabbit	No significant irritation
Titanium Dioxide	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Triethylene Glycol Dimethacrylate	Professio	Moderate irritant
	nal	
	judgeme	
	nt	
Diisopropylnaphthalene	Rabbit	Severe irritant
Amorphous Silica	Rabbit	No significant irritation
Hydroxypropyl Methacrylate	Rabbit	Moderate irritant
Cumene Hydroperoxide	Rabbit	Corrosive
Silica	Rabbit	No significant irritation
Acrylic Acid	Rabbit	Corrosive
Ethylene Glycol	Rabbit	Mild irritant
2,6-di-tert-Butyl-p-cresol	Rabbit	Mild irritant
N,N-Dimethyl-p-toluidine	Rabbit	No significant irritation
2,2'-(P-Tolylimino)diethanol	Rabbit	Corrosive
Titanium Dioxide	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
Triethylene Glycol Dimethacrylate	Human	Sensitizing
	and	
	animal	
Diisopropylnaphthalene	Guinea	Not classified
	pig	
Amorphous Silica	Human	Not classified
	and	
	animal	
Hydroxypropyl Methacrylate	Human	Sensitizing
	and	
	animal	
Silica	Human	Not classified
	and	
	animal	
Acrylic Acid	Guinea	Not classified
	pig	
Ethylene Glycol	Human	Not classified
1-Acetyl-2-Phenylhydrazine	Professio	Sensitizing
	nal	
	judgeme	
	nt	
2,6-di-tert-Butyl-p-cresol	Human	Not classified
N,N-Dimethyl-p-toluidine	Guinea	Sensitizing
	pig	
2,2'-(P-Tolylimino)diethanol	Mouse	Sensitizing
Titanium Dioxide	Human	Not classified
	and	
	animal	

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Triethylene Glycol Dimethacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Diisopropylnaphthalene	In Vitro	Not mutagenic
Diisopropylnaphthalene	In vivo	Not mutagenic
Amorphous Silica	In Vitro	Not mutagenic
Hydroxypropyl Methacrylate	In vivo	Not mutagenic
Hydroxypropyl Methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Cumene Hydroperoxide	In vivo	Not mutagenic
Cumene Hydroperoxide	In Vitro	Some positive data exist, but the data are not sufficient for classification
Silica	In Vitro	Not mutagenic
Acrylic Acid	In vivo	Not mutagenic
Acrylic Acid	In Vitro	Some positive data exist, but the data are not sufficient for classification
Ethylene Glycol	In Vitro	Not mutagenic
Ethylene Glycol	In vivo	Not mutagenic
1-Acetyl-2-Phenylhydrazine	In Vitro	Some positive data exist, but the data are not sufficient for classification
2,6-di-tert-Butyl-p-cresol	In Vitro	Not mutagenic
2,6-di-tert-Butyl-p-cresol	In vivo	Not mutagenic
N,N-Dimethyl-p-toluidine	In vivo	Not mutagenic
N,N-Dimethyl-p-toluidine	In Vitro	Some positive data exist, but the data are not sufficient for classification
2,2'-(P-Tolylimino)diethanol	In Vitro	Not mutagenic
Titanium Dioxide	In Vitro	Not mutagenic
Titanium Dioxide	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Triethylene Glycol Dimethacrylate	Dermal	Mouse	Not carcinogenic
Diisopropylnaphthalene	Ingestion	Rat	Not carcinogenic
Amorphous Silica	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Silica	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Acrylic Acid	Ingestion	Rat	Not carcinogenic
Acrylic Acid	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Ethylene Glycol	Ingestion	Multiple animal species	Not carcinogenic
2,6-di-tert-Butyl-p-cresol	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
N,N-Dimethyl-p-toluidine	Ingestion	Multiple animal species	Carcinogenic
Titanium Dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium Dioxide	Inhalation	Rat	Carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Triethylene Glycol Dimethacrylate	Ingestion	Not classified for female reproduction	Mouse	NOAEL 1 mg/kg/day	1 generation
Triethylene Glycol Dimethacrylate	Ingestion	Not classified for male reproduction	Mouse	NOAEL 1	1 generation

				mg/kg/day	
Triethylene Glycol Dimethacrylate	Ingestion	Not classified for development	Mouse	NOAEL 1 mg/kg/day	1 generation
Diisopropylnaphthalene	Ingestion	Not classified for development	Rat	NOAEL 625 mg/kg/day	during organogenesi s
Amorphous Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Amorphous Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Amorphous Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesi s
Hydroxypropyl Methacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
Hydroxypropyl Methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	49 days
Hydroxypropyl Methacrylate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation
Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesi s
Acrylic Acid	Ingestion	Not classified for female reproduction	Rat	NOAEL 460 mg/kg/day	2 generation
Acrylic Acid	Ingestion	Not classified for male reproduction	Rat	NOAEL 460 mg/kg/day	2 generation
Acrylic Acid	Inhalation	Not classified for development	Rat	NOAEL 1.1 mg/l	during organogenesi s
Acrylic Acid	Ingestion	Not classified for development	Rat	NOAEL 53 mg/kg/day	2 generation
Ethylene Glycol	Dermal	Not classified for development	Mouse	NOAEL 3,549 mg/kg/day	during organogenesi s
Ethylene Glycol	Ingestion	Not classified for development	Mouse	LOAEL 750 mg/kg/day	during organogenesi s
Ethylene Glycol	Inhalation	Not classified for development	Mouse	NOAEL 1,000 mg/kg/day	during organogenesi s
2,6-di-tert-Butyl-p-cresol	Ingestion	Not classified for female reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
2,6-di-tert-Butyl-p-cresol	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
2,6-di-tert-Butyl-p-cresol	Ingestion	Not classified for development	Rat	NOAEL 100 mg/kg/day	2 generation
N,N-Dimethyl-p-toluidine	Ingestion	Not classified for female reproduction	Rat	NOAEL 60 mg/kg/day	90 days

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Diisopropylnaphthalene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Hydroxypropyl Methacrylate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Cumene Hydroperoxide	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	occupational exposure

Page 11 **of** 15

Cumene Hydroperoxide	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not	occupational
					available	exposure
Cumene Hydroperoxide	Ingestion	central nervous	May cause drowsiness or	Professio	NOAEL Not	
		system depression	dizziness	nal	available	
				judgeme		
				nt		
Acrylic Acid	Inhalation	respiratory irritation	Some positive data exist, but the	Human	NOAEL Not	
			data are not sufficient for		available	
			classification			
Ethylene Glycol	Ingestion	heart nervous	Causes damage to organs	Human	NOAEL Not	poisoning
		system kidney			available	and/or abuse
		and/or bladder				
		respiratory system				
Ethylene Glycol	Ingestion	central nervous	May cause drowsiness or	Human	NOAEL Not	poisoning
•		system depression	dizziness		available	and/or abuse
Ethylene Glycol	Ingestion	liver	Not classified	Human	NOAEL Not	poisoning
-					available	and/or abuse
2,2'-(P-	Inhalation	respiratory irritation	Some positive data exist, but the	similar	NOAEL Not	
Tolylimino)diethanol			data are not sufficient for	health	available	
,			classification	hazards		

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Triethylene Glycol Dimethacrylate	Dermal	kidney and/or bladder blood	Not classified	Mouse	NOAEL 833 mg/kg/day	78 weeks
Diisopropylnaphthalene	Ingestion	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 170 mg/kg/day	6 months
Diisopropylnaphthalene	Ingestion	liver immune system kidney and/or bladder	Not classified	Rat	NOAEL 170 mg/kg/day	6 months
Amorphous Silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Hydroxypropyl Methacrylate	Inhalation	blood	Not classified	Rat	NOAEL 0.5 mg/l	21 days
Hydroxypropyl Methacrylate	Ingestion	hematopoietic system heart endocrine system liver immune system nervous system kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	41 days
Cumene Hydroperoxide	Inhalation	nervous system respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.2 mg/l	7 days
Cumene Hydroperoxide	Inhalation	heart liver kidney and/or bladder	Not classified	Rat	NOAEL 0.03 mg/l	90 days
Silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Ethylene Glycol	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 200 mg/kg/day	2 years
Ethylene Glycol	Ingestion	vascular system	Not classified	Rat	NOAEL 200 mg/kg/day	2 years
Ethylene Glycol	Ingestion	heart hematopoietic system liver immune system muscles	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
Ethylene Glycol	Ingestion	respiratory system	Not classified	Mouse	NOAEL 12,000 mg/kg/day	2 years
Ethylene Glycol	Ingestion	skin endocrine system bone, teeth, nails, and/or hair nervous system eyes	Not classified	Multiple animal species	NOAEL 1,000 mg/kg/day	2 years

Page 12 **of** 15

1-Acetyl-2-	Ingestion	hematopoietic	Causes damage to organs through	Dog	LOAEL 4	7 days
Phenylhydrazine		system	prolonged or repeated exposure	_	mg/kg/day	
2,6-di-tert-Butyl-p-cresol	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 250 mg/kg/day	28 days
2,6-di-tert-Butyl-p-cresol	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 500 mg/kg/day	2 generation
2,6-di-tert-Butyl-p-cresol	Ingestion	blood	Not classified	Rat	LOAEL 420 mg/kg/day	40 days
2,6-di-tert-Butyl-p-cresol	Ingestion	endocrine system	Not classified	Rat	NOAEL 25 mg/kg/day	2 generation
2,6-di-tert-Butyl-p-cresol	Ingestion	heart	Not classified	Mouse	NOAEL 3,480 mg/kg/day	10 weeks
N,N-Dimethyl-p-toluidine	Ingestion	hematopoietic system	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 20 mg/kg/day	3 months
N,N-Dimethyl-p-toluidine	Ingestion	respiratory system	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 20 mg/kg/day	2 years
N,N-Dimethyl-p-toluidine	Ingestion	liver immune system kidney and/or bladder heart skin endocrine system gastrointestinal tract bone, teeth, nails, and/or hair muscles nervous system eyes vascular system	Not classified	Rat	NOAEL 60 mg/kg/day	2 years
Titanium Dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium Dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

Name	Value
Diisopropylnaphthalene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel

_ 10 -

during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Not applicable

Health Hazards

Carcinogenicity

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

Skin Corrosion or Irritation

Specific target organ toxicity (single or repeated exposure)

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
Saccharin	81-07-2	Trade Secret <= 2
Cumene Hydroperoxide	80-15-9	Trade Secret < 2

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

 Document Group:
 32-6787-9
 Version Number:
 4.02

 Issue Date:
 01/18/23
 Supercedes Date:
 09/10/21

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com