Safety Data Sheet

Document Group:	38-3347-2	**Version Number:**	1.11
Issue Date:	08/26/25	**Supersedes Date:**	06/18/25

SECTION 1: Identification

1.1. Product identifier
Wheel & Paint Iron DECON (Detailer) D1801 [D180101 D180105]

Product Identification Numbers
LB-1100-2635-4, LB-1100-2635-5, 14-1001-1950-3, 14-1001-1951-1, 14-1001-4463-4
7100206013, 7100203995, 7100283404

1.2. Recommended use and restrictions on use

Recommended use
Automotive, iron remover for wheels and paint

1.3. Supplier's details

MANUFACTURER:	Meguiar's, Inc.
DIVISION:	Meguiar's
ADDRESS:	213 Technology Dr, Irvine, CA 92618
Telephone:	1-800-347-5700

1.4. Emergency telephone number
CHEMTREC 1-800-424-9300 (24 hours)

SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

2.1. Hazard classification
Acute Toxicity (oral): Category 4.
Serious Eye Damage/Irritation: Category 2A.
Skin Sensitizer: Category 1A.

2.2. Label elements
Signal word
Warning

Symbols
Exclamation mark |

Pictograms

Hazard Statements
Harmful if swallowed.
Causes serious eye irritation.
May cause an allergic skin reaction.

Precautionary Statements
General:
Keep out of reach of children.

Prevention:
Avoid breathing dust/fume/gas/mist/vapors/spray.
Wear protective gloves and eye/face protection.
Do not eat, drink or smoke when using this product.
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.

Response:
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.
IF ON SKIN: Wash with plenty of soap and water.
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.
Rinse mouth.
IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

Disposal:
Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

3% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Water	7732-18-5	60 - 100
Acetic acid, mercapto-, monoammonium salt	5421-46-5	10 - 30 Trade Secret *
Ethoxydiglycol	111-90-0	1 - 5 Trade Secret *
Sodium Laureth Sulfate	68891-38-3	1 - 5 Trade Secret *
SODIUM XYLENE SULFONATE	1300-72-7	1 - 5 Trade Secret *
Butoxyethanol	111-76-2	0.5 - 1.5 Trade Secret *
Sodium Lauryl Sulfate	68585-47-7	0.5 - 1.5 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:
Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:
Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:
Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:
Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required
Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media
In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture
None inherent in this product.

Hazardous Decomposition or By-Products

Substance	Condition
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion

5.3. Special protective actions for fire-fighters
Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up
Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling
Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities
Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits
If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Butoxyethanol	111-76-2	OSHA	TWA:240 mg/m3(50 ppm)	SKIN
Butoxyethanol	111-76-2	ACGIH	TWA:20 ppm	A3: Confirmed animal carcin.
Ethoxydiglycol	111-90-0	AIHA	TWA:140 mg/m3(25 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists
AIHA : American Industrial Hygiene Association
CMRG : Chemical Manufacturer's Recommended Guidelines
OSHA : United States Department of Labor - Occupational Safety and Health Administration
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls
Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Full Face Shield
Indirect Vented Goggles

Skin/hand protection
Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

For prolonged or repeated contact, gloves made from the following material(s) are recommended (breakthrough times are >4 hours): Nitrile Rubber

Any glove recommended for prolonged/repeated contact is also suitable for short-term/splash contact.

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Full facepiece air-purifying respirator suitable for organic vapors or acid gases
Full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	
Physical state	Liquid
Color	Orange, Red
Odor	Sulfuric
Odor threshold	*No Data Available*
pH	6.3 - 7
Melting point	*No Data Available*
Boiling Point	212 ºF
Flash Point	Flash point > 93 °C (200 °F)
Evaporation rate	*No Data Available*
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	*No Data Available*
Flammable Limits(UEL)	*No Data Available*
Vapor Pressure	*No Data Available*
Vapor Density	*No Data Available*
Density	1.05 g/cm3
Specific Gravity	1.05 [*Ref Std:*WATER=1]
Solubility in Water	Complete
Solubility- non-water	*No Data Available*
Partition coefficient: n-octanol/ water	*No Data Available*
Autoignition temperature	*No Data Available*
Decomposition temperature	*No Data Available*
Viscosity	20 - 80 centipoise
Molecular weight	*No Data Available*

Volatile Organic Compounds	1.3 % weight [*Test Method:*calculated per CARB title 2]
Percent volatile	77.5 % weight [*Test Method:*Estimated]
VOC Less H2O & Exempt Solvents	196 g/l [*Test Method:*calculated SCAQMD rule 443.1]

SECTION 10: Stability and reactivity

10.1. Reactivity
This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability
Stable.

10.3. Possibility of hazardous reactions
Hazardous polymerization will not occur.

10.4. Conditions to avoid
Light

10.5. Incompatible materials
Strong acids
Strong oxidizing agents

10.6. Hazardous decomposition products

Substance	Condition
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:
Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Allergic Respiratory Reaction in sensitive people: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest.

Skin Contact:
Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:
Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the

cornea, and impaired vision.

Ingestion:
Harmful if swallowed. Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Toxicological Data
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >300 - =2,000 mg/kg
Acetic acid, mercapto-, monoammonium salt	Dermal	Rat	LD50 > 1,430 mg/kg
Acetic acid, mercapto-, monoammonium salt	Ingestion	Rat	LD50 >35, <142 mg/kg
Ethoxydiglycol	Dermal	Rabbit	LD50 9,143 mg/kg
Ethoxydiglycol	Ingestion	Rat	LD50 5,400 mg/kg
Sodium Laureth Sulfate	Dermal	Rat	LD50 > 2,000 mg/kg
Sodium Laureth Sulfate	Ingestion	Rat	LD50 2,870 mg/kg
SODIUM XYLENE SULFONATE	Dermal	Rabbit	LD50 > 2,000 mg/kg
SODIUM XYLENE SULFONATE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.4 mg/l
SODIUM XYLENE SULFONATE	Ingestion	Rat	LD50 7,200 mg/kg
Sodium Lauryl Sulfate	Ingestion	Rat	LD50 1,830 mg/kg
Sodium Lauryl Sulfate	Dermal	similar compounds	LD50 > 2,000 mg/kg
Butoxyethanol	Dermal	Guinea pig	LD50 > 2,000 mg/kg
Butoxyethanol	Inhalation-Vapor (4 hours)	Guinea pig	LC50 > 2.6 mg/l
Butoxyethanol	Ingestion	Guinea pig	LD50 1,200 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Acetic acid, mercapto-, monoammonium salt	Human and animal	Minimal irritation
Ethoxydiglycol	Rabbit	No significant irritation
Sodium Laureth Sulfate	Rabbit	Irritant
SODIUM XYLENE SULFONATE	Rabbit	Minimal irritation
Sodium Lauryl Sulfate	similar compounds	Irritant
Butoxyethanol	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
Acetic acid, mercapto-, monoammonium salt	Rabbit	No significant irritation
Ethoxydiglycol	Rabbit	Moderate irritant
Sodium Laureth Sulfate	Rabbit	Corrosive
SODIUM XYLENE SULFONATE	Rabbit	Moderate irritant
Sodium Lauryl Sulfate	similar	Corrosive

	compounds	
Butoxyethanol	Rabbit	Severe irritant

Skin Sensitization

Name	Species	Value
Acetic acid, mercapto-, monoammonium salt	Human and animal	Sensitizing
Ethoxydiglycol	Human	Not classified
Sodium Laureth Sulfate	Guinea pig	Not classified
SODIUM XYLENE SULFONATE	Guinea pig	Not classified
Sodium Lauryl Sulfate	similar compounds	Not classified
Butoxyethanol	Guinea pig	Not classified

Respiratory Sensitization

Name	Species	Value
Acetic acid, mercapto-, monoammonium salt	Human	Some positive data exist, but the data are not sufficient for classification

Germ Cell Mutagenicity

Name	Route	Value
Acetic acid, mercapto-, monoammonium salt	In Vitro	Not mutagenic
Ethoxydiglycol	In Vitro	Not mutagenic
Ethoxydiglycol	In vivo	Not mutagenic
Sodium Laureth Sulfate	In Vitro	Not mutagenic
Sodium Laureth Sulfate	In vivo	Not mutagenic
SODIUM XYLENE SULFONATE	In Vitro	Not mutagenic
Sodium Lauryl Sulfate	In Vitro	Not mutagenic
Butoxyethanol	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
SODIUM XYLENE SULFONATE	Dermal	Multiple animal species	Not carcinogenic
Butoxyethanol	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Ethoxydiglycol	Dermal	Not classified for development	Rat	NOAEL 5,500 mg/kg/day	during organogenesis
Ethoxydiglycol	Ingestion	Not classified for development	Mouse	NOAEL 5,500 mg/kg/day	during organogenesis
Ethoxydiglycol	Inhalation	Not classified for development	Rat	NOAEL 0.6 mg/l	during organogenesis
Ethoxydiglycol	Ingestion	Not classified for male reproduction	Rat	NOAEL 2,200	2 generation

				mg/kg/day	
Sodium Laureth Sulfate	Ingestion	Not classified for female reproduction	Rat	NOAEL 300 mg/kg/day	90 days
Sodium Laureth Sulfate	Ingestion	Not classified for male reproduction	Rat	NOAEL 300 mg/kg/day	90 days
Sodium Laureth Sulfate	Ingestion	Not classified for development	Rat	NOAEL 300 mg/kg/day	2 generation
SODIUM XYLENE SULFONATE	Ingestion	Not classified for development	Rabbit	NOAEL 1,000 mg/kg/day	during gestation
Butoxyethanol	Dermal	Not classified for development	Rat	NOAEL 1,760 mg/kg/day	during gestation
Butoxyethanol	Ingestion	Not classified for development	Rat	NOAEL 100 mg/kg/day	during organogenesis
Butoxyethanol	Inhalation	Not classified for development	Multiple animal species	NOAEL 0.48 mg/l	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Ethoxydiglycol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Sodium Laureth Sulfate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
SODIUM XYLENE SULFONATE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL not available	
Sodium Lauryl Sulfate	Inhalation	respiratory irritation	May cause respiratory irritation	similar compounds	NOAEL Not available	
Butoxyethanol	Dermal	endocrine system	Not classified	Rabbit	NOAEL 902 mg/kg	6 hours
Butoxyethanol	Dermal	liver	Not classified	Rabbit	LOAEL 72 mg/kg	not available
Butoxyethanol	Dermal	kidney and/or bladder	Not classified	Rabbit	LOAEL 451 mg/kg	6 hours
Butoxyethanol	Dermal	blood	Not classified	Multiple animal species	NOAEL Not available	
Butoxyethanol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Butoxyethanol	Inhalation	central nervous system depression	Not classified	Professional judgement	NOAEL Not available	
Butoxyethanol	Inhalation	blood	Not classified	Multiple animal species	NOAEL Not available	
Butoxyethanol	Ingestion	central nervous system depression	Not classified	Professional judgement	NOAEL Not available	
Butoxyethanol	Ingestion	blood	Not classified	Multiple animal species	NOAEL Not available	
Butoxyethanol	Ingestion	kidney and/or bladder	Not classified	Human	NOAEL Not available	poisoning and/or abuse

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure

						Duration
Ethoxydiglycol	Dermal	kidney and/or bladder	Not classified	Rabbit	NOAEL 1,000 mg/kg/day	12 weeks
Ethoxydiglycol	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Pig	NOAEL 167 mg/kg/day	90 days
Ethoxydiglycol	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 2,700 mg/kg/day	90 days
Ethoxydiglycol	Ingestion	endocrine system	Not classified	Rat	NOAEL 2,500 mg/kg/day	90 days
Ethoxydiglycol	Ingestion	heart | hematopoietic system | nervous system	Not classified	Mouse	NOAEL 8,100 mg/kg/day	90 days
Sodium Laureth Sulfate	Dermal	skin | heart | endocrine system | gastrointestinal tract | hematopoietic system | liver | immune system | nervous system | eyes | kidney and/or bladder | respiratory system | vascular system	Not classified	Mouse	NOAEL 6.91 mg/day	90 days
Sodium Laureth Sulfate	Ingestion	blood | eyes	Not classified	Rat	NOAEL 225 mg/kg/day	90 days
SODIUM XYLENE SULFONATE	Dermal	liver | heart | skin | endocrine system | gastrointestinal tract | bone, teeth, nails, and/or hair | hematopoietic system | immune system | nervous system | kidney and/or bladder | respiratory system	Not classified	Rat	NOAEL 500 mg/kg/day	14 weeks
SODIUM XYLENE SULFONATE	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 763 mg/kg/day	90 days
Butoxyethanol	Dermal	blood	Not classified	Multiple animal species	NOAEL Not available	not available
Butoxyethanol	Dermal	endocrine system	Not classified	Rabbit	NOAEL 150 mg/kg/day	90 days
Butoxyethanol	Inhalation	liver	Not classified	Rat	NOAEL 2.4 mg/l	14 weeks
Butoxyethanol	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 0.15 mg/l	14 weeks
Butoxyethanol	Inhalation	blood	Not classified	Rat	LOAEL 0.15 mg/l	6 months
Butoxyethanol	Inhalation	endocrine system	Not classified	Dog	LOAEL 1.9 mg/l	8 days
Butoxyethanol	Ingestion	blood	Not classified	Rat	LOAEL 69 mg/kg/day	13 weeks
Butoxyethanol	Ingestion	kidney and/or bladder	Not classified	Multiple animal species	NOAEL Not available	not available

Aspiration Hazard
For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information

on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact manufacturer for more information

EPCRA 311/312 Hazard Classifications:

Physical Hazards
Not applicable

Health Hazards
Acute toxicity
Respiratory or Skin Sensitization
Serious eye damage or eye irritation

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

Ingredient	C.A.S. No	% by Wt
Ethoxydiglycol (CAS NO SEQ548L1)	111-90-0	Trade Secret 1 - 5
Butoxyethanol (CAS NO SEQ548L1)	111-76-2	Trade Secret 0.5 - 1.5

15.2. State Regulations

Contact manufacturer for more information

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact manufacturer for more information

15.4. International Regulations

Contact manufacturer for more information

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	38-3347-2	**Version Number:**	1.11
Issue Date:	08/26/25	**Supersedes Date:**	06/18/25

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. Meguiar's Inc. MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the Meguiar's Inc. product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a Meguiar's Inc. product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Meguiar's Inc. product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

Meguiar's Inc. provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, Meguiar's Inc. makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from Meguiar's Inc.

Meguiar's, Inc. USA SDSs are available at www.Meguiars.com