



Safety Data Sheet

Copyright,2023, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|------------------------|-----------|-------------------------|----------|
| Document Group: | 08-8510-3 | Version Number: | 19.06 |
| Issue Date: | 08/23/23 | Supersedes Date: | 08/18/23 |

SECTION 1: Identification

1.1. Product identifier

3M™ Fire Barrier Water Tight Sealant 1000 NS

Product Identification Numbers

98-0400-5276-7, 98-0400-5278-3, 98-0400-5555-4
7000006377, 7000006378, 7010353044

1.2. Recommended use and restrictions on use

Recommended use

Fire Protection, This product is a watertight sealant that will help control the spread of fire, smoke and noxious gases.

1.3. Supplier's details

| | |
|----------------------|---|
| MANUFACTURER: | 3M |
| DIVISION: | Industrial Adhesives and Tapes Division |
| ADDRESS: | 3M Center, St. Paul, MN 55144-1000, USA |
| Telephone: | 1-888-3M HELPS (1-888-364-3577) |

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2A.
Skin Sensitizer: Category 1.
Carcinogenicity: Category 1B.
Specific Target Organ Toxicity (repeated exposure): Category 2.

2.2. Label elements

Signal word

Danger

Symbols

Exclamation mark | Health Hazard |

Pictograms

**Hazard Statements**

Causes serious eye irritation.
 May cause an allergic skin reaction.
 May cause cancer.

May cause damage to organs through prolonged or repeated exposure:
 blood or blood-forming organs |
 respiratory system |

Precautionary Statements**General:**

Keep out of reach of children.

Prevention:

Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 Wear protective gloves and eye/face protection.
 Wash thoroughly after handling.
 Contaminated work clothing must not be allowed out of the workplace.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 If eye irritation persists: Get medical advice/attention.
 IF ON SKIN: Wash with plenty of soap and water.
 If skin irritation or rash occurs: Get medical advice/attention.
 Wash contaminated clothing before reuse.
 IF exposed or concerned: Get medical advice/attention.

Storage:

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

Supplemental Information:

This product may release methyl ethyl ketoxime (CAS 96-29-7) during curing and/or when exposed to water or humid air. Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

2% of the mixture consists of ingredients of unknown acute oral toxicity.
 2% of the mixture consists of ingredients of unknown acute dermal toxicity.
 2% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|------------------------|------------|------------------------|
| Calcium Carbonate | 1317-65-3 | 15 - 40 Trade Secret * |
| Poly(Dimethylsiloxane) | 63148-62-9 | 15 - 40 Trade Secret * |

| | | |
|---|------------|---------------------------|
| Siloxanes and Silcones, Di-Me, Hydroxy-Terminated | 70131-67-8 | 15 - 40 Trade Secret * |
| Ketoxime Silane | 22984-54-9 | 3 - 7 Trade Secret * |
| Amorphous Silica | 7631-86-9 | 0.5 - 5 Trade Secret * |
| Pigments | Mixture | 1 - 2 Trade Secret * |
| Methyl ethyl ketone oxime | 96-29-7 | 0.01 - 1.2 Trade Secret * |
| (Trimethoxysilylpropyl)Ethylenediamine | 1760-24-3 | < 1 Trade Secret * |
| Octamethylcyclotetrasiloxane | 556-67-2 | < 0.1 Trade Secret * |

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Formaldehyde
Carbon monoxide
Carbon dioxide
Oxides of Nitrogen

Condition

During Combustion
During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from strong bases. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|---|------------|--------|---|---------------------|
| Calcium Carbonate | 1317-65-3 | OSHA | TWA(as total dust):15 mg/m ³ ;TWA(respirable fraction):5 mg/m ³ | |
| Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles | 1317-65-3 | ACGIH | TWA(inhalable particulates):10 mg/m ³ | |
| Particles (insoluble or poorly soluble) not otherwise specified, respirable particles | 1317-65-3 | ACGIH | TWA(respirable particles):3 mg/m ³ | |
| Octamethylcyclotetrasiloxane | 556-67-2 | AIHA | TWA:10 ppm | |
| DUST, INERT OR NUISANCE | 7631-86-9 | OSHA | TWA(as total dust):15 mg/m ³ ;TWA(as total dust):50 millions of particles/cu. ft.(15 mg/m ³);TWA(respirable fraction):5 mg/m ³ ;TWA(respirable fraction):15 millions of particles/cu. ft.(5 mg/m ³) | |
| Particles (insoluble or poorly | 7631-86-9 | ACGIH | TWA(inhalable | |

| | | | | |
|---|-----------|-------|-----------------------------------|-------------------|
| soluble) not otherwise specified, inhalable particles | | | particulates):10 mg/m3 | |
| Particles (insoluble or poorly soluble) not otherwise specified, respirable particles | 7631-86-9 | ACGIH | TWA(respirable particles):3 mg/m3 | |
| Methyl ethyl ketone oxime | 96-29-7 | AIHA | TWA:36 mg/m3(10 ppm) | Dermal Sensitizer |

ACGIH : American Conference of Governmental Industrial Hygienists
 AIHA : American Industrial Hygiene Association
 CMRG : Chemical Manufacturer's Recommended Guidelines
 OSHA : United States Department of Labor - Occupational Safety and Health Administration
 TWA: Time-Weighted-Average
 STEL: Short Term Exposure Limit
 CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

- Safety Glasses with side shields
- Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

- Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

| | |
|-----------------------|-------|
| Physical state | Solid |
| Color | Gray |

| | |
|--|--|
| Specific Physical Form: | Paste |
| Odor | Low Odor |
| Odor threshold | <i>No Data Available</i> |
| pH | <i>No Data Available</i> |
| Melting point | <i>No Data Available</i> |
| Boiling Point | <i>Not Applicable</i> |
| Flash Point | > 212 °F [<i>Test Method:</i> Closed Cup] |
| Evaporation rate | <i>Not Applicable</i> |
| Flammability (solid, gas) | Not Classified |
| Flammable Limits(LEL) | <i>Not Applicable</i> |
| Flammable Limits(UEL) | <i>Not Applicable</i> |
| Vapor Pressure | < 5 mmHg [<i>@ 25 °C</i>] |
| Vapor Density | >=1 [<i>Ref Std:</i> AIR=1] |
| Density | 1.32 g/cm ³ |
| Specific Gravity | 1.31 - 1.33 [<i>Ref Std:</i> WATER=1] |
| Solubility in Water | Nil |
| Solubility- non-water | <i>No Data Available</i> |
| Partition coefficient: n-octanol/ water | <i>No Data Available</i> |
| Autoignition temperature | <i>No Data Available</i> |
| Decomposition temperature | <i>No Data Available</i> |
| Viscosity | <i>No Data Available</i> |
| Molecular weight | <i>No Data Available</i> |
| Volatile Organic Compounds | <=4 % weight [<i>Test Method:</i> tested per EPA method 24] |
| VOC Less H₂O & Exempt Solvents | <=53 g/l [<i>Test Method:</i> tested per EPA method 24] |

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Not determined

10.5. Incompatible materials

Strong acids

Strong bases

Strong oxidizing agents

10.6. Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:

Hematopoietic Effects: Signs/symptoms may include generalized weakness, fatigue and alterations in numbers of circulating blood cells.

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Additional Information:

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|-----------------|------------------------|---------|--|
| Overall product | Dermal | | No data available; calculated ATE >5,000 mg/kg |
| Overall product | Inhalation-Vapor(4 hr) | | No data available; calculated ATE >50 mg/l |
| Overall product | Ingestion | | No data available; calculated ATE >5,000 mg/kg |

| | | | |
|---|--------------------------------|-------------------------|-----------------------------------|
| Calcium Carbonate | Dermal | Rat | LD50 > 2,000 mg/kg |
| Calcium Carbonate | Inhalation-Dust/Mist (4 hours) | Rat | LC50 3 mg/l |
| Calcium Carbonate | Ingestion | Rat | LD50 6,450 mg/kg |
| Siloxanes and Silcones, Di-Me, Hydroxy-Terminated | Dermal | Rabbit | LD50 > 16,000 mg/kg |
| Siloxanes and Silcones, Di-Me, Hydroxy-Terminated | Ingestion | Rat | LD50 > 64,000 mg/kg |
| Poly(Dimethylsiloxane) | Dermal | Rabbit | LD50 > 19,400 mg/kg |
| Poly(Dimethylsiloxane) | Ingestion | Rat | LD50 > 17,000 mg/kg |
| Amorphous Silica | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| Amorphous Silica | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 0.691 mg/l |
| Amorphous Silica | Ingestion | Rat | LD50 > 5,110 mg/kg |
| Ketoxime Silane | Dermal | Rat | LD50 > 2,000 mg/kg |
| Ketoxime Silane | Ingestion | Rat | LD50 2,260 mg/kg |
| Methyl ethyl ketone oxime | Dermal | official classification | LD50 1,100 mg/kg |
| Methyl ethyl ketone oxime | Ingestion | official classification | LD50 100 mg/kg |
| Methyl ethyl ketone oxime | Inhalation-Vapor | Rat | LC50 estimated to be 20 - 50 mg/l |
| (Trimethoxysilylpropyl)Ethylenediamine | Dermal | Rabbit | LD50 > 2,000 mg/kg |
| (Trimethoxysilylpropyl)Ethylenediamine | Inhalation-Dust/Mist (4 hours) | Rat | LC50 >1.49, <2.44 mg/l |
| (Trimethoxysilylpropyl)Ethylenediamine | Ingestion | Rat | LD50 1,897 mg/kg |
| Octamethylcyclotetrasiloxane | Dermal | Rat | LD50 > 2,400 mg/kg |
| Octamethylcyclotetrasiloxane | Inhalation-Dust/Mist (4 hours) | Rat | LC50 36 mg/l |
| Octamethylcyclotetrasiloxane | Ingestion | Rat | LD50 > 5,000 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|--|---------|---------------------------|
| Calcium Carbonate | Rabbit | No significant irritation |
| Poly(Dimethylsiloxane) | Rabbit | No significant irritation |
| Amorphous Silica | Rabbit | No significant irritation |
| Ketoxime Silane | Rabbit | No significant irritation |
| Methyl ethyl ketone oxime | Rabbit | Irritant |
| (Trimethoxysilylpropyl)Ethylenediamine | Rabbit | Mild irritant |
| Octamethylcyclotetrasiloxane | Rabbit | Minimal irritation |

Serious Eye Damage/Irritation

| Name | Species | Value |
|--|---------|---------------------------|
| Calcium Carbonate | Rabbit | No significant irritation |
| Poly(Dimethylsiloxane) | Rabbit | No significant irritation |
| Amorphous Silica | Rabbit | No significant irritation |
| Ketoxime Silane | Rabbit | Moderate irritant |
| Methyl ethyl ketone oxime | Rabbit | Corrosive |
| (Trimethoxysilylpropyl)Ethylenediamine | Rabbit | Corrosive |
| Octamethylcyclotetrasiloxane | Rabbit | No significant irritation |

Skin Sensitization

| Name | Species | Value |
|------------------|------------------|----------------|
| Amorphous Silica | Human and animal | Not classified |

| | | |
|--|-------------------------|----------------|
| Ketoxime Silane | Guinea pig | Sensitizing |
| Methyl ethyl ketone oxime | Guinea pig | Sensitizing |
| (Trimethoxysilylpropyl)Ethylenediamine | Multiple animal species | Sensitizing |
| Octamethylcyclotetrasiloxane | Human and animal | Not classified |

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

| Name | Route | Value |
|---|----------|--|
| Siloxanes and Silcones, Di-Me, Hydroxy-Terminated | In Vitro | Not mutagenic |
| Amorphous Silica | In Vitro | Not mutagenic |
| Ketoxime Silane | In Vitro | Not mutagenic |
| Methyl ethyl ketone oxime | In Vitro | Not mutagenic |
| Methyl ethyl ketone oxime | In vivo | Not mutagenic |
| (Trimethoxysilylpropyl)Ethylenediamine | In Vitro | Not mutagenic |
| (Trimethoxysilylpropyl)Ethylenediamine | In vivo | Not mutagenic |
| Octamethylcyclotetrasiloxane | In Vitro | Some positive data exist, but the data are not sufficient for classification |

Carcinogenicity

| Name | Route | Species | Value |
|---------------------------|---------------|-------------------------|--|
| Amorphous Silica | Not Specified | Mouse | Some positive data exist, but the data are not sufficient for classification |
| Methyl ethyl ketone oxime | Inhalation | Multiple animal species | Carcinogenic |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test Result | Exposure Duration |
|--|-----------|--|---------|-----------------------|--------------------------------|
| Calcium Carbonate | Ingestion | Not classified for development | Rat | NOAEL 625 mg/kg/day | prematuring & during gestation |
| Amorphous Silica | Ingestion | Not classified for female reproduction | Rat | NOAEL 509 mg/kg/day | 1 generation |
| Amorphous Silica | Ingestion | Not classified for male reproduction | Rat | NOAEL 497 mg/kg/day | 1 generation |
| Amorphous Silica | Ingestion | Not classified for development | Rat | NOAEL 1,350 mg/kg/day | during organogenesis |
| Ketoxime Silane | Ingestion | Not classified for female reproduction | Rat | NOAEL 250 mg/kg/day | prematuring into lactation |
| Ketoxime Silane | Ingestion | Not classified for male reproduction | Rat | NOAEL 250 mg/kg/day | 28 days |
| Ketoxime Silane | Ingestion | Not classified for development | Rat | NOAEL 250 mg/kg/day | prematuring into lactation |
| Methyl ethyl ketone oxime | Ingestion | Not classified for female reproduction | Rat | NOAEL 200 mg/kg/day | 2 generation |
| Methyl ethyl ketone oxime | Ingestion | Not classified for male reproduction | Rat | NOAEL 200 mg/kg/day | 2 generation |
| Methyl ethyl ketone oxime | Ingestion | Not classified for development | Rat | NOAEL 600 mg/kg/day | during organogenesis |
| (Trimethoxysilylpropyl)Ethylenediamine | Ingestion | Not classified for female reproduction | Rat | NOAEL 500 | prematuring |

| | | | | | |
|--|------------|--------------------------------------|--------|---------------------|----------------------|
| | | | | mg/kg/day | into lactation |
| (Trimethoxysilylpropyl)Ethylenediamine | Ingestion | Not classified for male reproduction | Rat | NOAEL 500 mg/kg/day | 28 days |
| (Trimethoxysilylpropyl)Ethylenediamine | Ingestion | Not classified for development | Rat | NOAEL 750 mg/kg/day | during gestation |
| Octamethylcyclotetrasiloxane | Inhalation | Not classified for male reproduction | Rat | NOAEL 8.5 mg/l | 2 generation |
| Octamethylcyclotetrasiloxane | Ingestion | Toxic to female reproduction | Rabbit | NOAEL 50 mg/kg/day | during organogenesis |
| Octamethylcyclotetrasiloxane | Inhalation | Toxic to female reproduction | Rat | NOAEL 3.6 mg/l | 2 generation |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|--|------------|-----------------------------------|--|------------------------|---------------------|-------------------|
| Calcium Carbonate | Inhalation | respiratory system | Not classified | Rat | NOAEL 0.812 mg/l | 90 minutes |
| Ketoxime Silane | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | similar health hazards | NOAEL Not available | |
| Methyl ethyl ketone oxime | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | similar health hazards | NOAEL Not available | |
| Methyl ethyl ketone oxime | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Rat | NOAEL 100 mg/kg | |
| (Trimethoxysilylpropyl)Ethylenediamine | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | similar health hazards | NOAEL Not available | |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|---------------------------|------------|--|--|---------|---------------------|-----------------------|
| Calcium Carbonate | Inhalation | respiratory system | Not classified | Human | NOAEL Not available | occupational exposure |
| Amorphous Silica | Inhalation | respiratory system silicosis | Not classified | Human | NOAEL Not available | occupational exposure |
| Ketoxime Silane | Ingestion | hematopoietic system | May cause damage to organs though prolonged or repeated exposure | Rat | NOAEL 10 mg/kg/day | 28 days |
| Ketoxime Silane | Ingestion | endocrine system liver nervous system kidney and/or bladder | Not classified | Rat | NOAEL 250 mg/kg/day | 28 days |
| Methyl ethyl ketone oxime | Inhalation | hematopoietic system | May cause damage to organs though prolonged or repeated exposure | Rat | NOAEL 0.36 mg/l | 28 days |
| Methyl ethyl ketone oxime | Inhalation | respiratory system | May cause damage to organs though prolonged or repeated exposure | Mouse | NOAEL 0.01 mg/l | 90 days |
| Methyl ethyl ketone oxime | Inhalation | liver | Not classified | Rat | NOAEL 1.44 mg/l | 28 days |
| Methyl ethyl ketone oxime | Ingestion | hematopoietic system | May cause damage to organs though prolonged or repeated exposure | Rat | NOAEL 25 mg/kg/day | 90 days |
| Methyl ethyl ketone oxime | Ingestion | respiratory system | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 100 mg/kg/day | 90 days |
| Methyl ethyl ketone oxime | Ingestion | nervous system | Not classified | Rat | NOAEL 400 mg/kg/day | 90 days |
| Methyl ethyl ketone oxime | Ingestion | liver kidney and/or bladder heart endocrine system bone, teeth, nails, | Not classified | Rat | NOAEL 335 mg/kg/day | 90 days |

| | | | | | | |
|---------------------------------------|------------|--|--|--------|-----------------------|--------------|
| | | and/or hair immune system | | | | |
| (Trimethoxysilylpropyl)Ethylendiamine | Dermal | skin endocrine system hematopoietic system kidney and/or bladder | Not classified | Rat | NOAEL 1,545 mg/kg/day | 11 days |
| (Trimethoxysilylpropyl)Ethylendiamine | Inhalation | respiratory system | May cause damage to organs though prolonged or repeated exposure | Rat | NOAEL 0.015 mg/l | 90 days |
| (Trimethoxysilylpropyl)Ethylendiamine | Inhalation | hematopoietic system eyes kidney and/or bladder | Not classified | Rat | NOAEL 0.044 mg/l | 90 days |
| (Trimethoxysilylpropyl)Ethylendiamine | Ingestion | hematopoietic system nervous system | Not classified | Rat | NOAEL 500 mg/kg/day | 28 days |
| Octamethylcyclotetrasiloxane | Dermal | hematopoietic system | Not classified | Rabbit | NOAEL 960 mg/kg/day | 3 weeks |
| Octamethylcyclotetrasiloxane | Inhalation | liver | Not classified | Rat | NOAEL 8.5 mg/l | 13 weeks |
| Octamethylcyclotetrasiloxane | Inhalation | endocrine system immune system kidney and/or bladder | Not classified | Rat | NOAEL 8.5 mg/l | 2 generation |
| Octamethylcyclotetrasiloxane | Inhalation | hematopoietic system | Not classified | Rat | NOAEL 8.5 mg/l | 13 weeks |
| Octamethylcyclotetrasiloxane | Ingestion | liver | Not classified | Rat | NOAEL 1,600 mg/kg/day | 2 weeks |

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Not applicable

Health Hazards

Carcinogenicity

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of the Korean Toxic Chemical Control Law. Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification**Health: 2 Flammability: 1 Instability: 0 Special Hazards: None**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification**Health: *2 Flammability: 1 Physical Hazard: 0 Personal Protection: X - See PPE section.**

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

| | | | |
|------------------------|-----------|-------------------------|----------|
| Document Group: | 08-8510-3 | Version Number: | 19.06 |
| Issue Date: | 08/23/23 | Supersedes Date: | 08/18/23 |

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com