



Safety Data Sheet

Copyright, 2026, Meguiar's Inc.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Meguiar's Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	39-4108-5	Version Number:	2.01
Issue Date:	03/19/26	Supersedes Date:	02/27/26

SECTION 1: Identification

1.1. Product identifier

Mirror Glaze® Ultra Pro Speed Compound (Professional) M110 [M11001 M11032]

Product Identification Numbers

14-1001-2048-5, 14-1001-2049-3
7100206012, 7100206011

1.2. Recommended use and restrictions on use

Recommended use

Automotive

1.3. Supplier's details

MANUFACTURER:	Meguiar's, Inc.
DIVISION:	Meguiar's
ADDRESS:	213 Technology Dr, Irvine, CA 92618
Telephone:	1-800-347-5700

1.4. Emergency telephone number

CHEMTREC 1-800-424-9300 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200.

2.2. Label elements

Signal word

Not applicable.

Symbols

Not applicable

Pictograms

Not applicable

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Water	7732-18-5	40 - 70
Aluminum Oxide	1344-28-1	10 - 30
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	7 - 13 Trade Secret *
GLYCERIN	56-81-5	1 - 5
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	64742-48-9	1 - 5 Trade Secret *
White mineral oil (petroleum)	8042-47-5	1 - 5 Trade Secret *
Triethanolamine	102-71-6	0.5 - 1.5
Plant Oil	Trade Secret*	0.5 - 1.5

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:

If exposed, flush eyes with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms develop, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Condition

Hydrocarbons
Carbon monoxide
Carbon dioxide

During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment.

7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Triethanolamine	102-71-6	ACGIH	TWA:5 mg/m ³	
Aluminum metal and insoluble	1344-28-1	ACGIH	TWA(respirable fraction):1	A4: Not class. as human

compounds, respirable fraction			mg/m3	carcin
Aluminum Oxide	1344-28-1	OSHA	TWA(as total dust):15 mg/m3;TWA(respirable fraction):5 mg/m3	
Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles	1344-28-1	ACGIH	TWA(inhalable particulates):10 mg/m3	
Particles (insoluble or poorly soluble) not otherwise specified, respirable particles	1344-28-1	ACGIH	TWA(respirable particles):3 mg/m3	
GLYCERIN	56-81-5	OSHA	TWA(as total dust):15 mg/m3;TWA(respirable fraction):5 mg/m3	
Mineral oil, excluding metal working fluids, pure, highly and severely refined, inhalable fraction	64742-47-8	ACGIH	TWA(inhalable fraction):5 mg/m3	A4: Not class. as human carcin
Mineral oil, excluding metal working fluids, pure, highly and severely refined, inhalable fraction	8042-47-5	ACGIH	TWA(inhalable fraction):5 mg/m3	A4: Not class. as human carcin
OIL MIST (MINERAL)	8042-47-5	OSHA	TWA(as mist):5 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

For prolonged or repeated contact, gloves made from the following material(s) are recommended (breakthrough times are >4 hours): Nitrile Rubber, Polymer laminate

Any glove recommended for prolonged/repeated contact is also suitable for short-term/splash contact.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part

of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Color	White
Odor	Hydrocarbon
Odor threshold	No Data Available
pH	8.2 - 8.9
Melting point/Freezing point	No Data Available
Boiling point/Initial boiling point/Boiling range	100 °C
Flash Point	>=93.3 °C [Test Method:Closed Cup]
Evaporation rate	No Data Available
Flammability	Not Applicable
Flammable Limits(LEL)	No Data Available
Flammable Limits(UEL)	No Data Available
Vapor Pressure	No Data Available
Relative Vapor Density	No Data Available
Density	1.09 g/cm ³
Relative Density	1.07 - 1.12 [Ref Std:WATER=1]
Water solubility	No Data Available
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Kinematic Viscosity	27,523 mm ² /sec
Volatile Organic Compounds	15 %
Percent volatile	74.2 % weight [Test Method:Estimated]
VOC Less H ₂ O & Exempt Solvents	461.9 g/l
Average particle size	No Data Available
Bulk density	No Data Available
Molecular weight	No Data Available
Softening point	No Data Available

* The values noted with an asterisk (*) in the above table are representative values based on testing of raw materials and selected products. Additionally, a material's characteristics may change depending upon the process and conditions of use at a facility, including further changes in particle size, or mixture with other materials. In order to obtain specific data for the material, we recommend the user conduct characterization testing based on the use factors at the specific facility.

Particle Characteristics	Not Applicable
--------------------------	----------------

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Not determined

10.5. Incompatible materials

Not determined

10.6. Hazardous decomposition products**Substance****Condition**

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects**Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Aluminum Oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminum Oxide	Inhalation-	Rat	LC50 > 2.3 mg/l

	Dust/Mist (4 hours)		
Aluminum Oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Ingestion	Rat	LD50 > 15,000 mg/kg
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Dermal	similar compound ds	LD50 > 5,000 mg/kg
White mineral oil (petroleum)	Dermal	Rabbit	LD50 > 2,000 mg/kg
White mineral oil (petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Dermal	similar compound ds	LD50 > 2,200 mg/kg
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Ingestion	similar compound ds	LD50 > 15,000 mg/kg
GLYCERIN	Dermal	Rabbit	LD50 estimated to be > 5,000 mg/kg
GLYCERIN	Ingestion	Rat	LD50 > 5,000 mg/kg
Plant Oil	Dermal		LD50 estimated to be > 5,000
Plant Oil	Ingestion		LD50 estimated to be > 5,000
Triethanolamine	Dermal	Rabbit	LD50 > 2,000 mg/kg
Triethanolamine	Ingestion	Rat	LD50 9,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Aluminum Oxide	Rabbit	No significant irritation
HYDROTREATED LIGHT PETROLEUM DISTILLATES	similar compound ds	Mild irritant
White mineral oil (petroleum)	Rabbit	No significant irritation
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	similar compound ds	Mild irritant
GLYCERIN	Rabbit	No significant irritation
Plant Oil	Human	Minimal irritation
Triethanolamine	Rabbit	Minimal irritation

Serious Eye Damage/Irritation

Name	Species	Value
Aluminum Oxide	Rabbit	No significant irritation
HYDROTREATED LIGHT PETROLEUM DISTILLATES	similar compound ds	No significant irritation
White mineral oil (petroleum)	Rabbit	Mild irritant
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	similar compound ds	No significant irritation
GLYCERIN	Rabbit	No significant irritation
Plant Oil	Rabbit	Mild irritant
Triethanolamine	Rabbit	Mild irritant

Skin Sensitization

Name	Species	Value
HYDROTREATED LIGHT PETROLEUM DISTILLATES	similar compound ds	Not classified
White mineral oil (petroleum)	Guinea pig	Not classified
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	similar compound ds	Not classified

GLYCERIN	Guinea pig	Not classified
Plant Oil	Human	Not classified
Triethanolamine	Human	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Aluminum Oxide	In Vitro	Not mutagenic
HYDROTREATED LIGHT PETROLEUM DISTILLATES	In Vitro	Not mutagenic
White mineral oil (petroleum)	In Vitro	Not mutagenic
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	In Vitro	Not mutagenic
Plant Oil	In Vitro	Not mutagenic
Plant Oil	In vivo	Not mutagenic
Triethanolamine	In Vitro	Not mutagenic
Triethanolamine	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Aluminum Oxide	Inhalation	Rat	Not carcinogenic
White mineral oil (petroleum)	Dermal	Mouse	Not carcinogenic
White mineral oil (petroleum)	Inhalation	Multiple animal species	Not carcinogenic
GLYCERIN	Ingestion	Mouse	Some positive data exist, but the data are not sufficient for classification
Triethanolamine	Dermal	Multiple animal species	Not carcinogenic
Triethanolamine	Ingestion	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
White mineral oil (petroleum)	Ingestion	Not classified for female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White mineral oil (petroleum)	Ingestion	Not classified for male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White mineral oil (petroleum)	Ingestion	Not classified for development	Rat	NOAEL 4,350 mg/kg/day	during gestation
GLYCERIN	Ingestion	Not classified for female reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
GLYCERIN	Ingestion	Not classified for male reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
GLYCERIN	Ingestion	Not classified for development	Rat	NOAEL 2,000 mg/kg/day	2 generation
Triethanolamine	Ingestion	Not classified for development	Mouse	NOAEL 1,125 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
HYDROTREATED	Inhalation	respiratory irritation	Some positive data exist, but the	similar	NOAEL Not	

LIGHT PETROLEUM DISTILLATES			data are not sufficient for classification	health hazards	available	
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Aluminum Oxide	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminum Oxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Inhalation	liver	Not classified	Rat	NOAEL 6 mg/l	13 weeks
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.5 mg/l	13 weeks
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 6 mg/l	13 weeks
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Ingestion	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 100 mg/kg/day	13 weeks
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Ingestion	eyes	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
White mineral oil (petroleum)	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,381 mg/kg/day	90 days
White mineral oil (petroleum)	Ingestion	liver	Not classified	Rat	NOAEL 1,336 mg/kg/day	90 days
White mineral oil (petroleum)	Ingestion	immune system	Not classified	Rat	NOAEL 1,336 mg/kg/day	90 days
GLYCERIN	Inhalation	respiratory system	Not classified	Rat	NOAEL 3.91 mg/l	14 days
GLYCERIN	Inhalation	heart	Not classified	Rat	NOAEL 3.91 mg/l	14 days
GLYCERIN	Inhalation	liver	Not classified	Rat	NOAEL 3.91 mg/l	14 days
GLYCERIN	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 3.91 mg/l	14 days
GLYCERIN	Ingestion	endocrine system	Not classified	Rat	NOAEL 10,000 mg/kg/day	2 years
GLYCERIN	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 10,000 mg/kg/day	2 years
GLYCERIN	Ingestion	liver	Not classified	Rat	NOAEL 10,000 mg/kg/day	2 years
GLYCERIN	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 10,000 mg/kg/day	2 years
Plant Oil	Ingestion	heart	Not classified	Rat	NOAEL 4,800 mg/kg/day	13 weeks

Plant Oil	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 4,800 mg/kg/day	13 weeks
Plant Oil	Ingestion	liver	Not classified	Rat	NOAEL 4,800 mg/kg/day	13 weeks
Plant Oil	Ingestion	kidney and/or bladder	Not classified	Mouse	NOAEL 13,000 mg/kg/day	13 weeks
Triethanolamine	Dermal	kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,000 mg/kg/day	2 years
Triethanolamine	Dermal	liver	Not classified	Mouse	NOAEL 4,000 mg/kg/day	13 weeks
Triethanolamine	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 1,000 mg/kg/day	2 years
Triethanolamine	Ingestion	liver	Not classified	Guinea pig	NOAEL 1,600 mg/kg/day	24 weeks

Aspiration Hazard

Name	Value
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Aspiration hazard
White mineral oil (petroleum)	Aspiration hazard
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Prior to disposal, consult all applicable authorities and regulations to insure proper classification. Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty and clean product containers may be disposed as non-hazardous waste. Consult your specific regulations and service providers to determine available options and requirements.

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact manufacturer for more information

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Not Applicable.

Health Hazards

Not Applicable.

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
Aluminum Oxide	1344-28-1	10 - 30

15.2. State Regulations

Contact manufacturer for more information

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact manufacturer for more information

15.4. International Regulations

Contact manufacturer for more information

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 1 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	39-4108-5	Version Number:	2.01
Issue Date:	03/19/26	Supersedes Date:	02/27/26

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. Meguiar's Inc. MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the Meguiar's Inc. product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a Meguiar's Inc. product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Meguiar's Inc. product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

Meguiar's Inc. provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, Meguiar's Inc. makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from Meguiar's Inc.

Meguiar's, Inc. USA SDSs are available at www.Meguiars.com