

Flashtape 1R

Adhesive tape

Ideally suited for high temperature applications

Features

- Multipurpose polyester tape, backed with a fully cured, pressure sensitive rubber adhesive.
- Excellent temperature and pressure resistance.
- Strips easily after use.
- Designed for use in areas where thicker, stronger tape is required.

Properties

Maximum cure temperature	204°C	400°F
Color	Green	
Adhesive	Rubber	
Carrier	Polyester	
Adhesive thickness	25.4µm	0.001"
Carrier thickness	25.4µm	0.001"
Total thickness	50.8µm	0.002"
Elongation at break	100%	

Availability

Standard width	25mm and 50mm	1" and 2"
Standard length	66m	72yd

Storage

No special storage conditions.

Health & safety

Handling of these products must conform to individual company guidelines and health and safety regulations.

All statements, technical information and recommendations contained in this data sheet are given in good faith and are based on tests believed to be reliable, but their accuracy and completeness are not guaranteed. They do not constitute an offer to any person and shall not be deemed to form the basis of any subsequent contract. All products are sold subject to the Cytec's Standard Terms and conditions of Sale. Accordingly, the user shall determine the suitability of the products for their intended use prior to purchase and shall assume all risk and liability in connection therewith. It is the responsibility of those wishing to sell items made from or embodying the products to inform the user of the properties of the products and the purposes for which they may be suitable, together with all precautionary measures required in handling those products. The information contained herein is under constant review and liable to be modified from time to time.

© Copyright 2012 – Cytec Process Materials (Keighley) Ltd, Cytec Process Materials (CA) Inc, Cytec Process Materials (Toulouse) Sarl, Cytec Process Materials (Milan) Srl. All rights reserved worldwide. All trademarks or registered trademarks are the property of their respective owners.