

# SM5127W

## Sealant tape

Ideally suited to wind energy and aerospace applications

### Features

- Formulated for wind energy and aerospace applications which require no to low temperature heating or curing.
- Formulated to seal most films to tools while positive vacuum is held for room temperature applications.
- Primary characteristics are high modulus, tensile strength and adhesion.
- For optimum results, strip tape from composite tools at ambient temperature.
- Use for multiple debulking cycles without reapplication.
- Manufactured by Schnee Morehead in the USA.

### Properties

Maximum cure temperature	121°C (bag to tool) 149°C (bag to bag)	250°F (bag to tool) 300°F (bag to bag)
Colour	Dark grey	

### Availability

Roll size	15.24m x 12mm x 3mm	50ft x 0.5in x 0.125in
Standard box contents	22 rolls per box	

### Storage

Must be stored in its original containers, below 27°C (81°F) and allowed to return to room temperature before use. Material has a 9 month shelf life from date of manufacture.

Must be stored flat.

Boxes should be stacked no more than 5 high.

### Health & safety

Handling of these products must conform to individual company guidelines and health and safety regulations.

All statements, technical information and recommendations contained in this data sheet are given in good faith and are based on tests believed to be reliable, but their accuracy and completeness are not guaranteed. They do not constitute an offer to any person and shall not be deemed to form the basis of any subsequent contract. All products are sold subject to the Cytec's Standard Terms and conditions of Sale. Accordingly, the user shall determine the suitability of the products for their intended use prior to purchase and shall assume all risk and liability in connection therewith. It is the responsibility of those wishing to sell items made from or embodying the products to inform the user of the properties of the products and the purposes for which they may be suitable, together with all precautionary measures required in handling those products. The information contained herein is under constant review and liable to be modified from time to time.

© Copyright 2012 – Cytec Process Materials (Keighley) Ltd, Cytec Process Materials (CA) Inc, Cytec Process Materials (Toulouse) Sarl, Cytec Process Materials (Milan) Srl. All rights reserved worldwide. All trademarks or registered trademarks are the property of their respective owners.