

# 60001

## Peel ply

Ideally suited to aerospace applications

### Features

- Porous, polyester peel ply.
- Heat set and scoured, for use directly against laminates or bond lines.
- Available coated and non-coated, depending on user requirement.
- Approved on a range of OEM specifications for composite manufacture and metal bonding.
- This product is particularly recommended for use with phenolic resin systems.
- Also recommended for composite manufacture and metal bonding applications.
- Manufactured by Precision Fabrics Group (PFG).

### Product variants

- NAT – Scoured and heat set finish
- IO – International Orange for easy identification
- VLP – Very Low Porosity finish
- SRB – Super Release Blue (inert, heat stabilised, cross-linked polymer finish)

### Properties

Maximum use temperature	204°C	400°F
Colour	Natural, blue and orange	
Fabric type	Polyester	
Fabric weight	85g/m <sup>2</sup>	2.5oz/yd <sup>2</sup>

### Availability

Standard width	1.52m	60in
Standard length	274m	300yd
	Slit widths available	

### Storage

No special storage conditions required.

### Health & safety

Handling of these products must conform to individual company guidelines and health and safety regulations.

All statements, technical information and recommendations contained in this data sheet are given in good faith and are based on tests believed to be reliable, but their accuracy and completeness are not guaranteed. They do not constitute an offer to any person and shall not be deemed to form the basis of any subsequent contract. All products are sold subject to the Cytec's Standard Terms and conditions of Sale. Accordingly, the user shall determine the suitability of the products for their intended use prior to purchase and shall assume all risk and liability in connection therewith. It is the responsibility of those wishing to sell items made from or embodying the products to inform the user of the properties of the products and the purposes for which they may be suitable, together with all precautionary measures required in handling those products. The information contained herein is under constant review and liable to be modified from time to time.

© Copyright 2012 – Cytec Process Materials (Keighley) Ltd, Cytec Process Materials (CA) Inc, Cytec Process Materials (Toulouse) Sarl, Cytec Process Materials (Milan) Srl. All rights reserved worldwide. All trademarks or registered trademarks are the property of their respective owners.