

SM5142W

Sealant tape

Ideally suited to aerospace and wind applications

Features

- Low temperature tape with high modulus, tensile strength and adhesion, formulated for the aerospace and wind energy markets.
- Seals most films to tools whilst positive vacuum is held for ambient applications.
- Use for multiple debulking cycles without reapplication.
- Non-hazardous, compatible with most substrates, including composite tools and film materials.
- For optimum results, strip take from composite tools at ambient temperature.
- Manufactured by Schnee Morehead in the USA.

Properties

Maximum cure temperature	121°C (bag to tool) 149°C (bag to bag)	250°F (bag to tool) 300°F (bag to bag)
Colour	Yellow	

Availability

Roll size	15.24m x 12mm x 3mm	50ft x 0.5in x 0.125in
Standard box contents	22 rolls per box	

Storage

Must be stored in its original containers, below 27°C (81°F).
Material has a 12 month shelf life from date of manufacture.
Must be stored flat.
Boxes should be stacked no more than 5 high.

Health & safety

Handling of these products must conform to individual company guidelines and health and safety regulations.

All statements, technical information and recommendations contained in this data sheet are given in good faith and are based on tests believed to be reliable, but their accuracy and completeness are not guaranteed. They do not constitute an offer to any person and shall not be deemed to form the basis of any subsequent contract. All products are sold subject to the Cytec's Standard Terms and conditions of Sale. Accordingly, the user shall determine the suitability of the products for their intended use prior to purchase and shall assume all risk and liability in connection therewith. It is the responsibility of those wishing to sell items made from or embodying the products to inform the user of the properties of the products and the purposes for which they may be suitable, together with all precautionary measures required in handling those products. The information contained herein is under constant review and liable to be modified from time to time.
© Copyright 2012 – Cytec Process Materials (Keighley) Ltd, Cytec Process Materials (CA) Inc, Cytec Process Materials (Toulouse) Sarl, Cytec Process Materials (Milan) Srl. All rights reserved worldwide. All trademarks or registered trademarks are the property of their respective owners.