

A2000

Release film

Ideally suited to debulking applications

Features

- Exhibits excellent release characteristics from all commonly used resin systems.
- Ideal for use in resin infusion applications.
- Available perforated or non-perforated
- Cost optimized release film suitable for use in a wide range of composite processing.
- High elongation and excellent conformability.
- Coloured red for ease of identification.
- Available perforated or non-perforated.

Properties

Maximum use temperature	150°C	302°F
Colour	Red	
Film	Blended polymer	
Standard perforation patterns	Contact us for full details	
Tensile strength (at break)	35MPa	5076psi
Elongation (at break)	500%	
Density	0.9g/cm ³	0.52oz/in ³

Availability

Thicknesses	30 and 50µm	0.001 and 0.002in
Standard width	Up to 1.52m	Up to 1.66yd
Standard length	400m	437yd

Storage

Store in original packaging

Health & safety

Handling of these products must conform to individual company guidelines and health and safety regulations.

All statements, technical information and recommendations contained in this data sheet are given in good faith and are based on tests believed to be reliable, but their accuracy and completeness are not guaranteed. They do not constitute an offer to any person and shall not be deemed to form the basis of any subsequent contract. All products are sold subject to the Cytec's Standard Terms and conditions of Sale. Accordingly, the user shall determine the suitability of the products for their intended use prior to purchase and shall assume all risk and liability in connection therewith. It is the responsibility of those wishing to sell items made from or embodying the products to inform the user of the properties of the products and the purposes for which they may be suitable, together with all precautionary measures required in handling those products. The information contained herein is under constant review and liable to be modified from time to time.

© Copyright 2012 – Cytec Process Materials (Keighley) Ltd, Cytec Process Materials (CA) Inc, Cytec Process Materials (Toulouse) Sarl, Cytec Process Materials (Milan) Srl. All rights reserved worldwide. All trademarks or registered trademarks are the property of their respective owners.