

SM5153

Sealant tape

Ideally suited to aerospace and wind energy applications

Features

- Developed for the aerospace and wind energy industries, and formulated to outperform all taped in its class.
- Can be used in debulking/compacting, envelope bagging, resin damming or as a pressure strip.
- With aggressive initial tack, it will maintain an airtight seal during the cure cycle.
- Strips cleanly from the tool with virtually no trace of residue.
- Easy de-bagging and minimal clean up between production cycles.
- Exhibits excellent usage and release characteristics, from composite and metal tools, in both oven and autoclave applications.
- Non hazardous, and has been shown to survive 30 debulking cycles.
- Manufactured by Schnee Morehead in the USA.

Properties

Maximum cure temperature	204°C	400°F
Colour	Yellow	

Availability

Roll size	15.24m x 12.7mm x 3mm	50ft x 0.5in x 0.125in
Standard box contents	32 rolls per box	

Storage

Must be stored in its original containers, below 27°C (81°F) and allowed to return to room temperature before use. Material has a 12 month shelf life from date of manufacture.

Must be stored flat.

Boxes should be stacked no more than 5 high.

Health & safety

Handling of these products must conform to individual company guidelines and health and safety regulations.

All statements, technical information and recommendations contained in this data sheet are given in good faith and are based on tests believed to be reliable, but their accuracy and completeness are not guaranteed. They do not constitute an offer to any person and shall not be deemed to form the basis of any subsequent contract. All products are sold subject to the Cytec's Standard Terms and conditions of Sale. Accordingly, the user shall determine the suitability of the products for their intended use prior to purchase and shall assume all risk and liability in connection therewith. It is the responsibility of those wishing to sell items made from or embodying the products to inform the user of the properties of the products and the purposes for which they may be suitable, together with all precautionary measures required in handling those products. The information contained herein is under constant review and liable to be modified from time to time.
© Copyright 2012 – Cytec Process Materials (Keighley) Ltd, Cytec Process Materials (CA) Inc, Cytec Process Materials (Toulouse) Sarl, Cytec Process Materials (Milan) Srl. All rights reserved worldwide. All trademarks or registered trademarks are the property of their respective owners.