

tesa® 64662

Industrial Grade Poly-coated Cloth Duct Tape

PRODUCT INFORMATION

Product Description

tesa® 64662 offers excellent tensile strength and hand-tearability. tesa® 64662 is available in a variety of colors. Excellent for draping, and securing as well as for demanding packaging, bundling, holding, seaming, sealing, protecting, wrapping and repairing applications.

Main Application

- Patching
- Packaging
- Seaming
- Sealing

Technical Data

■ Backing material	PE laminated cloth	■ Elongation at break	16 %
■ Total thickness	230 µm 9.1 mils	■ Tensile strength	42 N/cm 24 lbs/in
■ Type of adhesive	natural rubber	■ Temperature resistance (30 min)	93 °C 199 °F
■ Adhesion to steel	5.472 N/cm 50 oz/in	■ Mesh	27 count per square inch

Properties

■ Hand tearability	+	■ Abrasion resistance	o
■ Straight tear edges	+	■ Water resistance	o

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

For latest information on this product please visit <http://l.tesa.com/?ip=64662>

Page 1 of 1 / As of 10/23/14

tesa tape, inc.

5825 Carnegie Boulevard
Charlotte, NC 28209
Phone: 704 554 0707
Toll Free: 800 426 2181
Fax: 800 852 8831
customer care@tesatape.com

Technical Tape México S.A. de C.V.

Av. Santa Fe No. 170
German Centre P 6-3-3Col.
Lomas de Santa Fe
Mexico D.F. C.P. 01210
Phone: +52 (55) 5292 6978
Fax: +52 (55) 5292 6977