

## LIGHT DUTY GUM PAPER TAPE

### TYPICAL APPLICATIONS

- Light to medium duty packaging applications
- Internal packaging for items placed in a secondary container

### ADVANTAGES AND BENEFITS

- Aggressive adhesive that becomes part of the box
- 100% recyclable/biodegradable

### CONSTRUCTION

Overall Grade/Function: Light duty

Backing: Kraft paper

Adhesive: Starch fortified, odorless, non-toxic, water activated

### COLOR(S)



Natural (NAT)



White (WHI)



### STANDARD WIDTH(S)

2½ in 3 in

### STANDARD LENGTH(S)

600 ft

Contact your Shurtape sales representative for other available sizes.

### PHYSICAL PROPERTIES

	STANDARD	METRIC
Paper Sheet (Weight)	57 lbs	25.9 kg
MD Tensile Strength	44 lbs/in width	77.1 N/10 mm
CD Tensile Strength	20 lbs/in width	35 N/10 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

### APPLICABLE STANDARDS

ASTM D 1974-98 (2003); ASTM D 5749 Type II, Grade B; CID A-A-1492B

### STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.