

tesa® 4421

Medium Grade, High Shear Masking Tape

PRODUCT INFORMATION

Product Description

tesa® 4421 provides an excellent blend of value and performance due to its excellent paper strength, cured rubber adhesive, and high shear. tesa® 4421 performs under stress and temperatures where general-purpose products fail. It is a production grade masking tape which has been formulated to assure clean removal from a variety of substrates. tesa® 4421 also has excellent wet grab and should be used when general-purpose masking tapes do not perform adequately. Available Colors: Cream

Main Application

- Medium temperature masking applications
- Medium-duty bundling, holding, packaging, and splicing

Technical Data

■ Backing material	slightly-creped paper	■ Adhesion to steel	3.7 N/cm
■ Total thickness	147.32 µm		33.8 oz/in
	5.8 mils	■ Elongation at break	10 %
■ Type of adhesive	natural rubber	■ Tensile strength	36.8 N/cm
			21 lbs/in

For latest information on this product please visit <http://l.tesa.com/?ip=04421>

Page 1 of 1 / As of 09/12/14

tesa tape, inc.

5825 Carnegie Boulevard
Charlotte, NC 28209
Phone: 704 554 0707
Toll Free: 800 426 2181
Fax: 800 852 8831
customer@tesatape.com

Technical Tape México S.A. de C.V.

Av. Santa Fe No. 170
German Centre P 6-3-3Col.
Lomas de Santa Fe
Mexico D.F. C.P. 01210
Phone: +52 (55) 5292 6978
Fax: +52 (55) 5292 6977

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.