




## Multi-Purpose Duct Tape



<b>Backing:</b>	PE Coated Cloth
<b>Adhesive:</b>	Rubber
<b>Liner:</b>	N/A
<b>Colors:</b>	Silver, Black, White, Blue, Brown, Burgundy, Green, OD, Red, Tan, Yellow
<b>Specifications:</b>	Tested in accordance with UL 723
<b>Standard Sizes:</b>	48mm x 55m, 72mm x 55m

### Applications

- General repair
- Sealing off polyethylene waste disposal bags
- Bundling & securing carpets, padding and protective sheeting for the convention & hotel industry
- General purpose abatement & contractor uses
- Bundling, patching & mending
- Plumbing applications
- Color coding
- Heavy-duty box sealing

### Features

- PE-Coated Cloth Backing
- Natural rubber based adhesive
- Low VOC Content

### Benefits

- Good balance of strength & conformability
- Resists twisting & curling
- Available in 11 colors
- Moisture resistant
- Aggressive adhesion to smooth and rough surfaces
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

### Physical Properties

	Standard UOM	Metric UOM	Test Method
<b>Total Thickness</b>	9 mils	228.6 mic	ASTM D-1000
<b>Adhesion to Steel</b>	70 oz/in	7.7 N/cm	PSTC-101
<b>Tensile Strength</b>	24 lb/in	42.03 N/cm	ASTM D-1000
<b>Operating Temperature</b>	40-200°F	4-93°C	
<b>Elongation</b>	20%		ASTM D-1000
<b>Smoke Developed</b>	0		UL 723
<b>Flame Spread</b>	5		UL 723
<b>VOC Content</b>	<3 g/L		

Recommended Storage Conditions: 40-60% Humidity, 60°F-80°F  
 Standard Shelf Life (at 25C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.