


Mobile Home Close-Off Tape



Backing:	LDPE Film
Adhesive:	Rubber
Liner:	N/A
Colors:	Clear, White
Specifications:	N/A
Standard Sizes:	Incremental widths 1/4" - 54" x 108ft

Applications

- General purpose sealing
- Splicing and seaming
- Temporary hold down

Features

- LDPE Film
- Rubber Adhesive

Benefits

- Conformable for irregular surfaces
- Abrasion, solvent, and moisture resistant
- Stands up to mechanical and chemical wear
- Adheres well to a wide variety of surfaces
- Excellent surface wetability
- Solvent and moisture resistant

Typical Test Values

	Standard UOM		Metric UOM		Test Method
Total Thickness	5.5	mils	0.140	mm	PSTC-133
Substrate Thickness	4.5	mils	0.114	mm	PSTC-133
Adhesion to Steel	25	oz/in	2.74	N/cm	ASTM D-3330
Tensile Strength	11	lb/in	19.26	N/cm	ASTM D-3759
Elongation	400%				
Application Temperature	50 to 120 °F		10 to 49 °C		
Operating Temperature	-40 to 190 °F		-40 to 88 °C		

Recommended Storage Conditions: 40-60% Humidity, 60°F-80°F
 Standard Shelf Life (at 25C): 12 months from shipment date

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.