

tesa® 53900

Aluminum Foil Tape

PRODUCT INFORMATION

Product Description

tesa® 53900 combines a flexible, soft aluminum foil backing with an aggressive rubber adhesive and paper liner. This tape offers flexibility and adhesive strength that conforms to the most irregular contours. Available Colors: Silver

Main Application

- FSK facings
- Vapor barrier
- Sealing
- Duct board joints

Technical Data

■ Backing material	aluminum foil	■ Adhesion to steel	9.9 N/cm
■ Total thickness	101.6 µm 4 mils	■ Elongation at break	90.4 oz/in 3 %
■ Type of adhesive	natural rubber	■ Tensile strength	29.8 N/cm 17 lbs/in

For latest information on this product please visit <http://l.tesa.com/?ip=53900>

Page 1 of 1 / As of 09/12/14

tesa tape, inc.

5825 Carnegie Boulevard
Charlotte, NC 28209
Phone: 704 554 0707
Toll Free: 800 426 2181
Fax: 800 852 8831
customer@tesatape.com

<http://www.tesatape.com>

Technical Tape México S.A. de C.V.

Av. Santa Fe No. 170
German Centre P 6-3-3Col.
Lomas de Santa Fe
Mexico D.F. C.P. 01210
Phone: +52 (55) 5292 6978
Fax: +52 (55) 5292 6977

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.