


Heavy-Duty Permanent PE Film Tape



Backing:	Polyethylene Film
Adhesive:	Synthetic Rubber
Liner:	N/A
Colors:	Red, White
Specifications:	N/A
Standard Sizes:	48mm x 55m, 72mm x 55m, 96mm x 55m

Applications

- Seaming vapor barrier films and underlayment materials including 10, 15, and 20 mil films
- Concrete underlayment applications including patch, repair, and sealing penetrations coming through the slab
- Splicing and seaming heavy-weight materials subjected to high abrasion and stress
- Dissimilar metal tape
- Abatement industry: hang and patch heavy-duty PE sheeting where clean removal is not required

Features

- Polyethylene Film Backing
- Synthetic Rubber Adhesive
- Low VOC, Contains no heavy metals (such as lead and chromium)

Benefits

- Conformable and flexible
- Excellent durability and solvent resistance
- Low elongation for consistent surface bond
- Low permeability for vapor barrier sealing
- Pinked/Serrated Edge available for hand tearability
- Permanent, long-term bond
- Aggressive, high tack formulation for instant bond
- Excellent shear strength
- Maintains adhesive integrity for up to 12 days of outdoor exposure
- Environmentally friendly and safe to use

Typical Test Values

	Standard UOM		Metric UOM		Test Method
Total Thickness (Colors)	7.0	mils	0.178	mm	ASTM D-1000
Adhesion to Steel	125	oz/in	13.68	N/cm	PSTC-101
Adhesion to Backing	53	oz/in	5.80	N/cm	PSTC-101
Tensile Strength	25	lb/in	43.78	N/cm	ASTM D-1000
Shear Strength	>350 hours				ASTM D-3654
Permeance	0.11 US Perms				ASTM F1249
WVTR	0.22 g/100 in ² /24 hrs				ASTM F1249
Application Temperature	30 to 160 °F		-1 to 71 °C		
Operating Temperature	20 to 200 °F		-7 to 93 °C		
Elongation	85%				

Recommended Storage Conditions: 60-80 °F at 40-60% RH
 Standard Shelf Life (at 25 °C): 24 months from date of manufacture.

The information presented herein was prepared at BERRY GLOBAL, INC (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.