

# tesa® 4657

Temperature resistant acrylic coated cloth tape

## PRODUCT INFORMATION

### Product Description

tesa® 4657 is a high grade acrylic coated cloth tape. It is based on a 145 mesh woven cotton fabric and a thermosetting natural rubber adhesive.

tesa® 4657 is a very resilient cloth tape, often used for permanent hole covering in automotive applications and masking during industrial painting processes.

Features:

- removes without residue, even after high temperature exposure
- very aging-resistant (allowing for permanent applications)
- high resistance to paint solvents
- excellent tape for die-cuts, available as log roll with liner as tesa® 4657 PV9
- also available as low unwinding version tesa® 4657 PV 1
- available in 2 colors: black, grey

### Main Application

- Heat resistant masking during the production of vehicles and machines
- Window flange masking
- Repeated oven drying possible
- Permanent interior and exterior hole covering
- Covering of screw tap holes and drainage boreholes
- Partial masking during treatment with impregnating agents
- Fastening of flat cables e.g. on roof linings, door panels, mirrors
- Masking during electrostatic powder coating

### Technical Data

■ Backing material	acrylic-coated cloth	■ Elongation at break	7.5 %
■ Total thickness	290 µm 11.4 mils	■ Tensile strength	105 N/cm 60 lbs/in
■ Type of adhesive	thermosetting natural rubber	■ Temperature resistance (30 min)	180 °C 356 °F
■ Adhesion to steel	4.6 N/cm 42 oz/in	■ Mesh	145 count per square inch

### Properties

■ Hand tearability	++	■ Suitable for die cutting	yes
■ Straight tear edges	++	■ Certified according to	all major OEMs
■ Easy to remove	yes	■ Abrasion resistance	++
■ Easy to write on	yes	■ Water resistance	+

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

For latest information on this product please visit <http://l.tesa.com/?ip=04657>

Page 1 of 1 / As of 11/01/14

#### tesa tape, inc.

5825 Carnegie Boulevard  
Charlotte, NC 28209  
Phone: 704 554 0707  
Toll Free: 800 426 2181  
Fax: 800 852 8831  
customercare@tesatape.com

[www.tesatape.com](http://www.tesatape.com)

#### Technical Tape México S.A. de C.V.

Av. Santa Fe No. 170  
German Centre P 6-3-3Col.  
Lomas de Santa Fe  
Mexico D.F. C.P. 01210  
Phone: +52 (55) 5292 6978  
Fax: +52 (55) 5292 6977

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.