




## Premium UL181 B-FX Duct Tape



**Backing:** Printed Polyethylene Coated Cloth

**Adhesive:** Rubber

**Liner:** N/A

**Colors:** Metallic, Black, Silver

**Specifications:** UL181B-FX Listed

**Standard Sizes:** 48mm x 55M, 72mm x 55M

### Applications

- A superior closure system for Class 1 flexible air ducts and air connectors
- Challenging bonding, protecting, bundling, and repair applications

### Features & Benefits

- High strength PE Coated Cloth Backing
- Aggressive Natural Rubber Adhesive
- UL181B-FX Listed
- Low VOC Content
- Tough and durable
- Conformable to wrap ducts for an effective seal
- Excellent bond to sheet metal and other surfaces
- High strength to withstand vertical pull from the weight of the duct system
- Resistant to moisture and mold growth
- Meets code requirements and can contribute toward requirements for EA Credit 1 (Optimize Energy Performance) under LEED®
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

### Physical Properties

	Standard UOM	Metric UOM	Test Method
<b>Total Thickness</b>	14 mils	355.6 mic	ASTM D-1000
<b>Adhesion to Steel</b>	45 oz/in	4.93 N/cm	PSTC-101
<b>Adhesion to Backing</b>	35 oz/in	3.83 N/cm	PSTC-101
<b>Tensile Strength</b>	29 lb/in	50.79 N/cm	ASTM D-1000
<b>Smoke Developed</b>	15		ASTM E-84
<b>Flame Spread</b>	15		ASTM E-84
<b>Operating Temperature</b>	40-200°F	4-93°C	
<b>VOC Content</b>	<1 g/L		

Recommended Storage Conditions: 40-60% Humidity, 60°F - 80°F  
Standard Shelf Life (at 25C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.