




Professional Grade Duct Tape (Metallic)



Backing

Adhesive

Backing: Metallized PE Coated Cloth

Adhesive: Rubber

Liner: N/A

Colors: Metallic

Specifications: Tested in accordance with UL 723

Standard Sizes: 48mm x 55m, 72mm x 55m

Applications

- Duct sealing and HVAC contractor uses
- Maintenance applications in manufacturing environments
- General repair
- Bundling, patching, and mending

Features

- Metallized PE-Coated Cloth Backing
- Natural rubber based adhesive
- Low VOC Content

Excellent balance of tensile strength and

- tearability
- Aggressive adhesion to rough surfaces
- Superior holding power for hanging applications

Benefits

 Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Physical Properties

	Standard UOM	Metric UOM	Test Method	
Total Thickness	11 mils	279.4 mic	ASTM D-1000	
Adhesion to Steel	70 oz/in	7.7 N/cm	PSTC-101	
Adhesion to Backing	39 oz/in	4.3 N/cm	PSTC-101	
Tensile Strength	24 lb/in	42 N/cm	ASTM D-1000	
Elongation	24%		ASTM D-1000	
Operating Temperature	40 to 200 °F	4 to 93 °C		
Smoke Developed	5			
Flame Spread	10			
VOC Content	<1 g/L			

Recommended Storage Conditions: 40-60% Humidity, 60°F-80°F Standard Shelf Life (at 25C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the users' information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.

