



Revision Number: 002.1

Issue date: 08/12/2011

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE EA 9696 030UNS AERO known as HYSOL EA 9696 .030 PSF UNS
IDH number: 611484
Product type: Adhesive for the Aerospace Industry
Item number: AF9113512
Region: United States
Company address: Henkel Corporation
 2850 Willow Pass Road
 Bay Point, California 94565
Contact information: Telephone: 925.458.8000 Fax: 925.458.8030
 MEDICAL EMERGENCY Phone: Poison Control Center
 1-877-671-4608 (toll free) or 1-303-592-1711
 TRANSPORT EMERGENCY Phone: CHEMTREC
 1-800-424-9300 (toll free) or 1-703-527-3887
 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Physical state:	Solid	HEALTH:	*2
Color:	Green	FLAMMABILITY:	1
Odor:	Slight	PHYSICAL HAZARD:	1
		Personal Protection:	See MSDS Section 8

WARNING: MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.
 MAY CAUSE ALLERGIC SKIN REACTION.

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects

Inhalation: May cause respiratory tract irritation.
Skin contact: This product may cause irritation to the skin. May cause allergic skin reaction.
Eye contact: This product may cause irritation to the eyes.
Ingestion: Not expected under normal conditions of use.

Existing conditions aggravated by exposure: Eye, skin, and respiratory disorders.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Modified epoxy resin	Unknown	30 - 60
Epoxy resin	Proprietary	30 - 60
Modified epoxy resin	Unknown	1 - 5
Bisphenol A Diglycidyl Ether	1675-54-3	1 - 5
Guanidine derivative	Proprietary	1 - 5

4. FIRST AID MEASURES

Inhalation: If inhaled, immediately remove the affected person to fresh air. If symptoms develop and persist, get medical attention.

Skin contact:	Immediately wash skin thoroughly with soap and water. If symptoms develop and persist, get medical attention.
Eye contact:	In case of contact with the eyes, rinse immediately with plenty of water for 15 minutes, and seek immediate medical attention.
Ingestion:	Get immediate medical attention. Do not induce vomiting. Never give anything by mouth to a victim who is unconscious or is having convulsions.
Notes to physician:	Treat symptomatically and supportively.

5. FIRE FIGHTING MEASURES

Flash point:	> 200 °F (> 93.33 °C) ; Estimated
Autoignition temperature:	Not applicable
Flammable/Explosive limits - lower:	Not determined
Flammable/Explosive limits - upper:	Not determined
Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear full protective clothing. Wear self-contained breathing apparatus.
Unusual fire or explosion hazards:	May liberate large quantities of dense, foul-smelling smoke which may contain unidentified toxic gasses.
Hazardous combustion products:	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Oxides of nitrogen.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Prevent further leakage or spillage if safe to do so. Wear appropriate protective equipment and clothing during clean-up. Do not allow product to enter sewer or waterways.
Clean-up methods:	Scrape up spilled material and place in a closed container for disposal. Dispose of according to Federal, State and local governmental regulations.

7. HANDLING AND STORAGE

Handling:	Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Do not breathe fumes or dust from this material. Do not take internally.
Storage:	Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Modified epoxy resin	None	None	None	None
Epoxy resin	None	None	None	None
Modified epoxy resin	None	None	None	None
Bisphenol A Diglycidyl Ether	None	None	None	None
Guanidine derivative	None	None	None	None

Engineering controls:	Ventilation should effectively remove and prevent buildup of any dust generated from the handling of this product.
Respiratory protection:	When dusts or thermal processing fumes are generated and ventilation is not sufficient to effectively remove them, appropriate NIOSH/MSHA approved respiratory protection must be provided.
Eye/face protection:	Safety goggles or safety glasses with side shields.
Skin protection:	Wear impervious gloves for prolonged contact. Use of impervious apron and boots are recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Solid
Color:	Green
Odor:	Slight
Odor threshold:	Not available
pH:	Not available
Vapor pressure:	Nil
Boiling point/range:	Not applicable
Melting point/ range:	Not determined
Specific gravity:	Not applicable
Vapor density:	> 1
Flash point:	> 200 °F (> 93.33 °C) ; Estimated
Flammable/Explosive limits - lower:	Not determined
Flammable/Explosive limits - upper:	Not determined
Autoignition temperature:	Not applicable
Evaporation rate:	Not determined
Solubility in water:	Negligible
Partition coefficient (n-octanol/water):	Not determined
VOC content:	< 10 g/l per SCAQMD Rule 1124 [EPA Test Method 24/304-91] (estimated)

10. STABILITY AND REACTIVITY

Stability:	Stable at normal conditions.
Hazardous reactions:	May occur.
Hazardous decomposition products:	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Oxides of nitrogen.
Incompatible materials:	Keep away from strong oxidizing agents, strong Lewis or mineral acids.
Conditions to avoid:	Avoid heating masses of film greater than 1 pound (0.454 kg) total. Avoid heating unless curing surfaces to be bonded. Failure to observe these precautions may result in excessive heat build-up causing an exotherm. The exotherm has the potential for release of toxic gasses.

11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Modified epoxy resin	No	No	No
Epoxy resin	No	No	No
Modified epoxy resin	No	No	No
Bisphenol A Diglycidyl Ether	No	No	No
Guanidine derivative	No	No	No

Hazardous components	Health Effects/Target Organs
Modified epoxy resin	No Data
Epoxy resin	Allergen, Irritant
Modified epoxy resin	No Data
Bisphenol A Diglycidyl Ether	Allergen, Central nervous system, Irritant, Liver, Respiratory
Guanidine derivative	Allergen, Central nervous system, Eyes, Irritant

12. ECOLOGICAL INFORMATION

Ecological information: Toxic to aquatic organisms

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

Hazardous waste number: Material, if discarded, is not expected to be a characteristic hazardous waste under RCRA.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act inventory.

TSCA 12(b) Export Notification: None above reporting de minimus

CERCLA/SARA Section 302 EHS: None above reporting de minimus

CERCLA/SARA Section 311/312: Immediate Health, Delayed Health

CERCLA/SARA 313: None above reporting de minimus

California Proposition 65:

This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status:

One or more components are not listed on, and are not exempt from listing on either the Domestic Substances List or the Non-Domestic Substances List.

WHMIS hazard class:

D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format.

Prepared by: Mark Mau, Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.