

tesa® 51132

Surface protection film

PRODUCT INFORMATION

Product Description

tesa® 51132 is a self adhesive film that has been developed for the protection of various surfaces, especially interior parts of automobiles like carpets, dashboards and door sills during storage, assembly and transportation.
tesa® 51132 consists of a PE backing coated with an water based acrylic adhesive.

Technical Data

■ Backing material	PE film	■ Adhesion to steel	2.8 N/cm
■ Total thickness	85 µm	■ Elongation at break	250 %
■ Type of adhesive	acrylic	■ Tensile strength	15 N/cm

Properties

■ Easy to remove	yes	■ Scratch resistance	+
------------------	-----	----------------------	---

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

Additional Info

User benefits:

- Cost saving due to reduction in rectification and final repair
- No special equipment needed, ensuring simple, low cost application and removal processes
- Good adhesion to the range of different surfaces like PP, ABS, textile.
- Easy disposal. Both film and adhesive system are environmentally friendly

For latest information on this product please visit <http://l.tesa.com/?ip=51132>

Page 1 of 1 / As of 10/23/14

tesa SE

Quickbornstraße 24
20253 Hamburg
Germany
Phone: +49 (40) 4909 101

tesa SE
A Beiersdorf Company

www.tesa.com

tesa tape inc.

5825 Carnegie Boulevard
Charlotte, N.C. 28209
United States of America
Phone: +1 (704) 554 0707
Fax: +1 (704) 553 5634
www.tesatape.com

tesa tape Asia Pacific Pte. Ltd.

9 North Buona Vista Drive
#04-01 The Metropolis
Tower 1
Singapore 138588
Tel: +65 6697 9888
Fax: +65 6659 6390
www.tesa-asia.com

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.