

**ECONOMY GRADE  
PRINTABLE UPVC FILM PACKAGING TAPE**

**TYPICAL APPLICATIONS**

- Sealing cartons, particularly those with recycled fiber content, heavy ink coverage or rough surfaces
- Use when sub-freezing temperatures and/or moisture are factors

**ADVANTAGES AND BENEFITS**

- Aggressive adhesive reduces application time because excessive rub-down is not necessary
- Excellent choice when sub-freezing temperatures and moisture are factors
- May be used on printed stock and recycled paper

**CONSTRUCTION**

Overall Grade/Function: Economy  
Backing: Unplasticized polyvinylchloride (UPVC) film  
Adhesive: Natural rubber



**COLOR(S)**



**STANDARD WIDTH(S)                  STANDARD LENGTH(S)**

48 mm                                  50 m

Contact your Shurtape sales representative for other available sizes.

**PHYSICAL PROPERTIES**

	<b>STANDARD</b>	<b>METRIC</b>
Tensile Strength	23 lbs/in width	40.3 N/10 mm
Adhesion to Stainless Steel	13 oz/in width	1.42 N/10 mm
Thickness	1.9 mils	0.05 mm
Elongation	60%	60%
Service Temperature Range	0 F to 150 F	-18 C to 66 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

**APPLICABLE STANDARDS**

CID A-A-1689B, Type II

**STORAGE & USAGE CONDITIONS**

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

\*Shurtape® is a registered trademark of Shurtape Technologies, LLC  
Form# TDS-VF-719-08/28/2013