

ShurWRAP® PROTECTIVE FILM TAPE

TYPICAL APPLICATIONS

- Seals spiral and rectangular galvanized ductwork for clean room installations, duct storage & transportation
- For hand use applications

ADVANTAGES AND BENEFITS

- Protects ducts from contaminants and contamination occurring from dust, dirt, moisture & insects
- Increased elongation from other films for duct sealants
- Easy removal without residue
- Cold weather adhesive

CONSTRUCTION

Overall Grade/Function: Protective Film
Backing: Polyolefin film
Adhesive: Water-based (emulsion) acrylic

COLOR(S)

 Translucent/Matte (CLR)

STANDARD WIDTH(S)

24 in 36 in 609.6 mm 914.4 mm 200 ft 60.96 m

Contact your Shurtape sales representative for other available sizes.

STANDARD LENGTH(S)

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile MD	7.8 lbs/in width	13.7 N/10 mm
Adhesion to Stainless Steel	13 oz/in width	1.42 N/10 mm
Adhesion to Backing	5.8 oz/in width	0.63 N/10 mm
Tape Gauge	2.5 mils	0.06 mm
Elongation MD	1200%	1200%
Service Temperature Range	-26 F to 260 F	-32 C to 127 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE STANDARDS

US Green Building Council – LEED® Point contributor product

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 24 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.



*Shurtape® is a registered trademark of Shurtape Technologies, LLC

Form# TDS-PF-220-12/16/2013