

Vac-Pak® E4760

Release film

Ideally suited to aerospace applications

Features

- Clear or blue tinted modified polymer release film providing excellent release capabilities from epoxy, phenolic, polyester and other resin systems without contamination.
- Specifically developed for use in mild contours and flat panel applications.
- With 300% elongation and 204°C (400°F) capabilities, this is an economical alternative.
- Available perforated or non-perforated.

Properties

Maximum use temperature	204°C	400°F
Colour	Clear and blue	
Film	PMP	
Standard perforation patterns	Contact us for full details	
Tensile strength (at break)	36MPa	4400psi
Elongation (at break)	300%	
Yield	46.6m ² /kg	228 ft ² /lb/mil

Availability

Thicknesses	38 and 51µm	0.0015 and 0.002in
Standard widths	Up to 1.83m	Up to 72in
Standard length	Up to 549m	Up to 600yd

Storage

Store in original packaging

Health & safety

Handling of these products must conform to individual company guidelines and health and safety regulations.

All statements, technical information and recommendations contained in this data sheet are given in good faith and are based on tests believed to be reliable, but their accuracy and completeness are not guaranteed. They do not constitute an offer to any person and shall not be deemed to form the basis of any subsequent contract. All products are sold subject to the Cytec's Standard Terms and conditions of Sale. Accordingly, the user shall determine the suitability of the products for their intended use prior to purchase and shall assume all risk and liability in connection therewith. It is the responsibility of those wishing to sell items made from or embodying the products to inform the user of the properties of the products and the purposes for which they may be suitable, together with all precautionary measures required in handling those products. The information contained herein is under constant review and liable to be modified from time to time.

© Copyright 2012 – Cytec Process Materials (Keighley) Ltd, Cytec Process Materials (CA) Inc, Cytec Process Materials (Toulouse) Sarl, Cytec Process Materials (Milan) Srl. All rights reserved worldwide. All trademarks or registered trademarks are the property of their respective owners.