




Professional Grade Duct Tape (Metallic)



Backing:	Metallized PE Coated Cloth	
Adhesive:	Rubber	
Liner:	N/A	
Colors:	Metallic	
Specifications	5:	Tested in accordance with UL 723
Standard Sizes:		48mm x 55m, 72mm x 55m

Applications

- Duct sealing and HVAC contractor uses
- Maintenance applications in manufacturing environments
- General repair
- Bundling, patching, and mending

Features	Benefits
Metallized PE-Coated Cloth Backing	 Excellent balance of tensile strength and tearability
Natural Rubber Based Adhesive	Aggressive adhesion to rough surfacesSuperior holding power for hanging applications
Low VOC Content	 Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED[®]

Physical Properties

	<i>i i</i>			
	Standard UOM	Metric UOM	Test Method	
Total Thickness	11 mils	279.4 mic	ASTM D-1000	
Adhesion to Steel	70 oz/in	7.7 N/cm	PSTC-101	
Adhesion to Backing	39 oz/in	4.3 N/cm	PSTC-101	
Tensile Strength	24 lb/in	42 N/cm	ASTM D-1000	
Elongation	24%		ASTM D-1000	
Operating Temperature	40 to 200 °F	4 to 93 °C		
Smoke Developed	5			
Flame Spread	10			
VOC Content	<1 g/L			

Recommended Storage Conditions: 40-60% Humidity, 60°F-80°F Standard Shelf Life (at 25C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.



25 Forge Pkwy Franklin, MA 02038 1-800-343-7875 Fax 1-800-328-4822 www.berryplastics.com Nijverheidsstraat 10 2260 Oevel (Westerlo) Belgium 32-014-722500 Fax 32-014-722570 6/18/13