

Vac-Pak® E7760W

Release film

Ideally suited to aerospace applications

Features

- High modulus film suitable for use with all commonly used resin systems up to 204°C (400°F).
- May be a suitable alternative to other, higher elongation and PVF films.
- Works well with ATL/AFP applications.
- Excellent film for mildly contoured or flat parts as it lies flat and smooth with few wrinkling issues, which are often experienced with other, more pliable, films.
- NDT detectable.

Properties

Maximum use temperature	204°C	400°F
Colour	Matt white	
Film	PET based	
Standard perforation patterns	Contact us for details	
Tensile strength (at break)	179MPa	26000psi
Elongation (at break)	100%	
Yield	28m ² /kg	137 ft ² /lb/mil

Availability

Thickness	25 and 50µm	0.001 and 0.002in
Standard width	1.22m	48in
Standard length	304.8m	1000ft

Storage

Store in original packaging

Health & safety

Handling of these products must conform to individual company guidelines and health and safety regulations.

All statements, technical information and recommendations contained in this data sheet are given in good faith and are based on tests believed to be reliable, but their accuracy and completeness are not guaranteed. They do not constitute an offer to any person and shall not be deemed to form the basis of any subsequent contract. All products are sold subject to the Cytec's Standard Terms and conditions of Sale. Accordingly, the user shall determine the suitability of the products for their intended use prior to purchase and shall assume all risk and liability in connection therewith. It is the responsibility of those wishing to sell items made from or embodying the products to inform the user of the properties of the products and the purposes for which they may be suitable, together with all precautionary measures required in handling those products. The information contained herein is under constant review and liable to be modified from time to time.

© Copyright 2012 – Cytec Process Materials (Keighley) Ltd, Cytec Process Materials (CA) Inc, Cytec Process Materials (Toulouse) Sarl, Cytec Process Materials (Milan) Srl. All rights reserved worldwide. All trademarks or registered trademarks are the property of their respective owners.