




Premium Military Grade Duct Tape



Backing: PE Coated Cloth

Adhesive: Rubber

Liner: N/A

Colors: Olive Drab, Black

Specifications: ASTM D -5486 Type IV Class 1 (supercedes PPP-

T-60D & E Type IV, Class 1), DPM 871-3

NSN 7510-00-074-4961

Standard Sizes: 48mm x 55m, 72mm x 55m

Applications

Waterproof packaging for military and aerospace applications

Media blast protection & surface masking

Challenging repair, bundling and seaming applications

Features Benefits

PE-Coated Cloth Backing

• High tensile strength for difficult applications

- Extremely conformable
- Crisp, straight tear
- Natural Rubber Based Adhesive

 Moisture, solvent & abrasion resistant
 - Aggressive adhesion to all surfaces

Physical Properties

	Standard UOM	Metric UOM	Test Method
Total Thickness	12 mils	305 mic	ASTM D-1000
Adhesion to Steel	95 oz/in	10.5 N/cm	PSTC-101
Adhesion to Backing	40 oz/in	4.4 N/cm	PSTC-101
Tensile Strength	50 lb/in	87.6 N/cm	ASTM D-1000
Elongation	13%		ASTM D-1000
Operating Temperature	40 to 200 °F	4 to 93 °C	
VOC Content	<1 g/L		

Recommended Storage Conditions: 40-60% Humidity, 60°F-80°F Standard Shelf Life (at 25C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.

