






UL181B-FX Approved Film Tape



Backing: Printed OPP Film

Adhesive: Acrylic

Liner: N/A

Colors: Metallic, Black

Specifications: UL181B-FX Listed

Standard Sizes: 48mm x 110M, 72mm x 110M

Applications

- Tough, contractor grade closure system for Class 1 flexible air ducts and connectors
- Sealing reflective and bubble insulation

Suitable for metal to metal connections in **HVAC** and refrigeration applications

Features & Benefits

OPP Backing

UL181B-FX Listed

Low VOC Content

LEADERSHIP BY DESIGN

- Tough and durable
- Hand tearable for ease of use
- easy inspection Acrylic Adhesive
 - Solvent-Free for reduced odor
 - Aggressive, high tack bond
 - Mold and moisture resistant
 - Meets code requirements and can contribute toward requirements for EA Credit 1 (Optimize Energy Performance) under LEED®

High visibility print (red on metallic, white on black) for

Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Physical Properties

	Standard UOM	Metric UOM	Test Method
Total Thickness	3.1 mils	78.74 N/cm	ASTM D-1000
Adhesion to Steel	45 oz/in	4.93 N/cm	PSTC-101
Adhesion to Backing	35 oz/in	3.83 N/cm	PSTC-101
Tensile Strength	34 lb/in	59.54 N/cm	ASTM D-1000
Operating Temperature	-10 to 250 ° F	-23 to 121 °C	
VOC Content	0 g/L		

Recommended Storage Conditions: 40-60% Humidity, 60°F - 80°F Standard Shelf Life (at 25C): 24 months from date of manufacture.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility. Nijverheidsstraat 10