


# Nashua<sup>®</sup> V1100

## **Utility Grade Masking Tape**



Backing

**Adhesive** 

**Backing:** Crepe Paper

**Adhesive:** Rubber

Liner: N/A

**Colors:** Natural

**Specifications:** N/A

**Standard Sizes:** 18mm x 55M, 24mm x 55M, 36mm x 55M,

48mm x 55M

#### **Applications**

General purpose masking tape for the building

• Light bundling, packaging and labelling and paint industry

Ideal for home paint masking applications

#### **Benefits Features**

•	Crepe Paper Backing	Hand Tearable
		<ul> <li>Conformable</li> </ul>
		<ul> <li>Holds up to most paints and other moisture</li> </ul>
•	Rubber Adhesive	<ul> <li>Good bond to most surfaces</li> </ul>
		<ul> <li>Clean removal for up to 1-3 days</li> </ul>

### **Physical Properties**

	Standard UOM	Metric UOM	Test Method
Total Thickness	4.8 mils	121.92 mic	ASTM D-1000
Adhesion to Steel	42 oz/in	4.6 N/cm	PSTC-101
Tensile Strength	16 lb/in	28.02 N/cm	ASTM D-1000
Elongation	8%		
<b>Operating Temperature</b>	40 - 150° F	4 - 65° C	

Recommended Storage Conditions: 40-60% Humidity, 60°F-80°F Standard Shelf Life (at 25C): 12 months from date of manufacture.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.

