





Backing:	Woven Polypr	opylene
Adhesive:	N/A	
Liner:	N/A	
Colors:	Yellow/Black, I	Red/Black, Red, Yellow
Specification	s: N/A	
Standard Siz	es: 2"x200	Ft, 2"x50Yd

Applications

• Re-usable barricade for marking hazardous and restricted areas.

• Blocking off construction sites, road repairs, and other hazardous areas.

	Features	Benefits
•	Woven Polypropylene	 Easy to use - just tie and untie Durable & re-useable Chemical, moisture and abrasion resistant - stands up to the elements High visibility

Physical Properties					
	Standard UOM	Metric UOM	Test Method		
Total Thickness	24 mils	609.6 mic	ASTM D-1000		
Tensile Strength	460 lb/in	805.58 N/cm	PSTC-101		
Elongation	100%				
Max Performance Temp	250° F	121° C			

Recommended Storage Conditions: 40-60% Humidity, 60°F-80°F

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.



25 Forge Pkwy Franklin, MA 02038 1-800-343-7875 Fax 1-800-328-4822 www.berryplastics.com Nijverheidsstraat 10 2260 Oevel (Westerlo) Belgium 32-014-722500 Fax 32-014-722570 6/26/2011