

# 780

## Anti-Skid Tape



**Backing:** Polymeric Film w/Mineral Particulate

**Adhesive:** Rubber Based

**Liner:** Paper

**Colors:** Black

**Specifications:** N/A

**Standard Sizes:** 50mm x 5M

### Applications

- Apply to a variety of surfaces to create a non-skid surface on stairs, factory floors, steel ramps, construction zones.
- General purpose skid resistance for most surfaces.

### Features

- Mineral Particulate Backing
- Rubber Adhesive

### Benefits

- Abrasion resistant, non-skid surface
- Durable
- Aggressive bond to a variety of surfaces
- Moisture and solvent resistant

### Physical Properties

	Standard UOM	Metric UOM	Test Method
<b>Total Thickness</b>	22 mils	558.8 mic	ASTM D-1000
<b>Adhesion to Steel</b>	32 oz/in	3.5 N/cm	PSTC-101
<b>Tensile Strength</b>	152 lb/in	266.19 N/cm	ASTM D-1000
<b>Elongation</b>	200%		
<b>Max Performance Temp</b>	176° F	80° C	

Recommended Storage Conditions: 40-60% Humidity, 60°F-80°F

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.