

HIGH TEMPERATURE FOIL FLUE TAPE

TYPICAL APPLICATIONS

- Seals and stops leaks from dryer vents, flue pipes and hot air ducts
- Application capable in extreme high, low, environmental and humid temperature conditions
- Adheres well to metal ducts, insulation and many irregular surfaces
- General protection tape in various high temperature patching, holding and splicing applications
- Seals metal flue pipe joints on non-wood and non-coal burning stoves, furnaces and external components of dryer vents

ADVANTAGES AND BENEFITS

- Lined
- Heat-resistant surface
- Green Point Contributor Product
- Tested in Accordance with UL 723

CONSTRUCTION

Overall Grade/Function: Industrial/Flue Tape
 Backing: Aluminum Foil
 Adhesive: Silicone
 Liner: Film Liner

COLOR(S)

 Silver (SIL)

STANDARD WIDTH(S)

3 in

STANDARD LENGTH(S)

50 yd

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	15.4 lbs/in width	26.9 N/10 mm
Adhesion to Stainless Steel	45.6 oz/in width	4.99 N/10 mm
Thickness (with liner)	12.8 mils	0.32 mm
Thickness (without liner)	4.2 mils	0.10 mm
Elongation	3.9%	3.9%
Application Temperature Range	-60 F to 600 F	-51.1 C to 315.5 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE STANDARDS

FSI 0/SDI 0; Tested in Accordance with UL 723; US Green Building Council – LEED® Point contributor product

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a dry area, between 60 F and 80 F, away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

NOT RECOMMENDED for use on wood or coal burning stoves.



*Shurtape® is a registered trademark of Shurtape Technologies, LLC

Form# TDS-AF-600-08/25/2014