

P-14

GENERAL PURPOSE ALUMINUM FOILTAPE

PRODUCT DESCRIPTION

P-14 combines the durability and weatherability of aluminum foil with a high performance acrylic adhesive adding to its performance ability in the aerospace and electrical markets.

FEATURES

- The aluminum foil is naturally resistant to water vapor and vapor transmission.
- The P-14 acrylic adhesive is resistant to most solvents and acids.
- Its high level of tack ensures a “quick stick” to most surfaces.
- P-14 is very conformable over contoured surfaces.

PRODUCT CONSTRUCTION

ALUMINUM FOIL
ACRYLIC

APPLICATION

- The P-14 general purpose aluminum foil tape can be die cut to create masking dots for repetitive masking applications.
- This tape is also appropriate for use as a moisture and vapor barrier, heat reflecting, use on cooling and/or heating coils, sealing of HVAC equipment, wrapping of underground cables and much more.

PROPERTIES, CERTIFICATIONS AND SPECIFICATIONS

Backing Material	Dead soft aluminum foil	
Adhesive	Acrylic	
Color	Aluminum	
	Imperial	Metric
Foil Thickness	3.0 mil	0.076 mm
Total Tape Thickness	4.3 mil	0.109 mm
Adhesion to Steel	40 oz/in	4.4 N/10 mm
Tensile Strength	26 lbs/in	46 N/10mm
Elongation	5%	5%

*CAUTION: The above are typical values and should not be used in writing specifications. Customer is responsible to ensure product meets intended application requirements before approved for use.

GENERAL STORAGE CONDITIONS

Best stored between 50°F-80°F / 10°C-27°C, 25-50% relative humidity; out of direct sunlight.

PRECAUTION REMINDER

Surface should be clean, free of oil, moisture and dirt before applying. Pressure-sensitive adhesive tapes may require pressure by roller, hand or press when applying. Not doing so may affect the general properties and appearance. Please inspect your surface prior to application; this tape may not adhere well to extremely uneven or distorted surfaces. Please remember to allow adequate time for full adhesive strength.

WARRANTY INFORMATION

The following is made in lieu of all warranties, expressed or implied, including the warranty of merchantability and fitness for a particular or ordinary purpose. NITTO DENKO AMERICA warrants that its products meet the applicable specifications at the time of shipment from our warehouse and NITTO DENKO AMERICA's sole obligation shall be to replace any such quantity of the product which fails to meet NITTO DENKO AMERICA's specifications or to issue a credit for such merchandise for a period of six (6) months from the date of shipment.

NITTO DENKO AMERICA MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

NITTO DENKO AMERICA shall not be liable for any injury, loss or damage, direct or consequential, arising out of or in connection with the use or the inability to use the product, nor shall any recovery of any kind in total against NITTO DENKO AMERICA be greater in amount than the purchased price of the specific material sold causing the alleged loss, damage or injury. Before using, buyer shall be responsible to determine the suitability of the product for his intended use, and buyer assumes all risk and liability in connection therewith. The foregoing may not be altered except by an agreement signed by an officer of NITTO DENKO AMERICA.

Any delays in or failure by either party hereto in the performance of any obligations hereunder shall be excused if and to the extent caused by occurrences beyond such party's reasonable control, including Acts of God, strikes or other labor disturbances, war, whether declared or not, fire, inability to secure transportation or any other cause or causes which cannot be reasonably controlled by such party.