

BR100

Release fabric

Ideally suited to resin rich applications

Features

- Fluorocarbon coated, light weight porous nylon fabric.
- Release coating ensures easier stripping of the fabric from resin rich composites.
- Tight weave construction gives close control of resin bleed.
- The material is supplied pink in colour for identification purposes.
- When using release fabrics on composite laminates that will be subject to secondary bonding or painting operations, there is a potential for minor transfer onto the component, despite the release solution being fully polymerised. It is therefore recommended that prior to bonding or painting the laminate should be suitably prepared (industry standard method is preparation by slight abrading or sanding the surface followed by cleaning with an approved solvent).

Properties

Maximum cure temperature	204°C	400°F
Colour	Pink	
Fabric type	Nylon	
Fabric weight	60g/m ²	1.77oz/yd ²
Release coating	Fluorocarbon	

Availability

Standard width	1.52m	60in
Standard length	100m	109yd
	Slit widths available	

Storage

No special storage conditions required.

Health & safety

Handling of these products must conform to individual company guidelines and health and safety regulations.

All statements, technical information and recommendations contained in this data sheet are given in good faith and are based on tests believed to be reliable, but their accuracy and completeness are not guaranteed. They do not constitute an offer to any person and shall not be deemed to form the basis of any subsequent contract. All products are sold subject to the Cytec's Standard Terms and conditions of Sale. Accordingly, the user shall determine the suitability of the products for their intended use prior to purchase and shall assume all risk and liability in connection therewith. It is the responsibility of those wishing to sell items made from or embodying the products to inform the user of the properties of the products and the purposes for which they may be suitable, together with all precautionary measures required in handling those products. The information contained herein is under constant review and liable to be modified from time to time.

© Copyright 2012 – Cytec Process Materials (Keighley) Ltd, Cytec Process Materials (CA) Inc, Cytec Process Materials (Toulouse) Sarl, Cytec Process Materials (Milan) Srl. All rights reserved worldwide. All trademarks or registered trademarks are the property of their respective owners.