

VP 500



CONTRACTOR GRADE EMBOSSED WHITE VINYL TAPE

TYPICAL APPLICATIONS

- Seaming and patching white vinyl faced insulation

ADVANTAGES AND BENEFITS

- Aggressive acrylic adhesive
- Lined
- Embossed white backing

CONSTRUCTION

Overall Grade/Function: Contractor
Backing: Embossed white vinyl
Adhesive: Acrylic

COLOR(S)



STANDARD WIDTH(S)

72 mm

STANDARD LENGTH(S)

50 yd

Contact your Shurtape sales representative for other available sizes.



PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	10 lbs/in width	17.5 N/10 mm
Adhesion to Stainless Steel	40 oz/in width	4.37 N/10 mm
Thickness (without liner)	4.3 mils	0.11 mm
Thickness (with liner)	7.0 mils	0.18 mm
Elongation	70%	70%
Service Temperature Range	20 F to 176 F	-7 C to 80 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE STANDARDS

Tested in accordance with UL 723; FSI 5/SDI 10

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

*Shurtape® is a registered trademark of Shurtape Technologies, LLC

Form# TDS-VP-500-11/20/2013